

Best of Texas

Landscapes



Maintenance Check List

Installation Completion Date: 9.17.15

Address: 137 Finnel Cr.

The following items have been provided and explained to the irrigation system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative

Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



Irrigator/Date

Irrigation Technician/ Date

Best of Texas

Landscapes



PO BOX 776
HUTTO, TX 78634

(512)228-4833
(512)852-9633 fax

Zone #	Description	Head Type	Run Time(Minutes)
1-7, 18	Beds	spray Bubbler	10.12
8-15	Turf	Sprays	25
16-17	Turf	Rotors	45

Month	Average Cycles
Jan.	3
Feb.	3
March	4
April	4
May	7
June	9
July	11
Aug.	11
Sept.	9
Oct.	6
Nov.	4
Dec.	3

MAINTENANCE ITEMS

- Backflow device – Test Annually (Call Louis Sinclair 563-8762)
- Y-strainer – Check annually for debris
- Heads – Run system monthly to check for leaks or broken nozzles
- Valve covers – Trim grass around cover to expose
- Controller – Check seasonally for correct run times
- Winter – Run system briefly every 2 weeks if system remains in off position

Irrigation

Quantity	Symbol	Description	Part Number	Pressure	Flow	Radius
Sprinklers						
62	☉	Rain Bird 10H - 1804	10H	30 psi	0.79 gpm	10 ft
23	☉	Rain Bird 10Q	10Q	30 psi	0.39 gpm	10 ft
1	☉	Rain Bird 1300A-F	1300AF	30 psi	1.7 gpm	0 ft
2	☉	Rain Bird 5000-MPR-30-H - 5004-PL-PC	MPR-30-H	45 psi	2.96 gpm	30 ft
6	☉	Rain Bird 5000-MPR-30-Q - 5004-PL-PC	MPR-30-Q	45 psi	1.4 gpm	30 ft
73	☉	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	8 ft
44	☉	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	8 ft

Meters/Pumps		
1	M	

Backflow Devices		
1	☉	Febco 715 - 1"

Control Valves		
19	☉	Rain Bird 100-DVF

Y-Strainers / Filters		
1	☉	Febco 650A-1"

Irrigation Accessories		
1	☉	Nelson 9501-100IN
1	☉	Rain Bird E-4c
1	☉	Rain Bird RSD-BEx

Lateral Line Pipe		
1910 ft	---	Class 200 1"

Mainline Pipe		
295 ft	---	Class 200 1"


Water Source #1	
Meter Size	5/8 inch meter
Static Pressure	65 psi
Elevation Change	0 ft

Service Line Information	
Pipe Category	Class 200 PVC
Pipe Size	Class 200 1"
Length	5 ft
Velocity	5 fps


Recommendations	
Maximum Recommended Flow	13 gpm
Available Working Pressure	58.39 psi

137 FINNELL CV.

Design pressure all zones 65psi.



JASON STUBBLEFIELD
9/17/2015



1" = 20'

