

# Best of Texas

Landscapes



## Maintenance Check List

Installation Completion Date: 9.23.15

Address: 6001 Cassena Cv.

The following items have been provided and explained to the irrigation system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

\_\_\_\_\_  
Irrigation system owner/representative

\_\_\_\_\_  
Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



\_\_\_\_\_  
Irrigator/Date

\_\_\_\_\_  
Irrigation Technician/ Date

# Best of Texas

## Landscapes



PO BOX 776  
HUTTO, TX 78634

(512)228-4833  
(512)852-9633 fax

Zone #	Description	Head Type	Run Time(Minutes)
1	Bed	Spray Bobbler	10-12
2-8	Turf	Sprays	25
9-10	Turf	Rotors	45

Month	Average Cycles
Jan.	3
Feb.	3
March	4
April	4
May	7
June	9
July	11
Aug.	11
Sept.	9
Oct.	6
Nov.	4
Dec.	3

### MAINTENANCE ITEMS

- Backflow device – Test Annually (Call Louis Sinclair 563-8762)
- Y-strainer – Check annually for debris
- Heads – Run system monthly to check for leaks or broken nozzles
- Valve covers – Trim grass around cover to expose
- Controller – Check seasonally for correct run times
- Winter – Run system briefly every 2 weeks if system remains in off position

**Irrigation**

Quantity	Symbol	Description	Part Number	Pressure	Flow	Radius
<b>Sprinklers</b>						
8	●	Rain Bird 10F - 1804	10F	30 psi	1.58 gpm	10 ft
41	●	Rain Bird 10H - 1804	10H	30 psi	0.79 gpm	10 ft
37	●	Rain Bird 10Q	10Q	30 psi	0.39 gpm	10 ft
2	○	Rain Bird 1300A-F	1300AF	30 psi	1.7 gpm	0 ft
6	●	Rain Bird 5000-MPR-30-Q - 5004-PL-PC	MPR-30-Q	45 psi	1.4 gpm	30 ft
8	●	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	8 ft
7	●	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	8 ft

<b>Meters/Pumps</b>		
1	M	

<b>Backflow Devices</b>		
1	BD	Febco 715 - 1"

<b>Control Valves</b>		
11	V	Rain Bird 100-DVF

<b>Y-Strainers / Filters</b>		
1	Y	Febco 650A-1"

<b>Irrigation Accessories</b>		
1	NS	Nelson 9501-100IN
1	E-4c	Rain Bird E-4c
1	RSD-BEx	Rain Bird RSD-BEx

<b>Lateral Line Pipe</b>		
928 ft	---	Class 200 1"

<b>Mainline Pipe</b>		
244 ft	---	Class 200 1"

**Water Source #1**

Meter Size	5/8 inch meter
Static Pressure	65 psi
Elevation Change	0 ft

**Service Line Information**


Pipe Category	Class 200 PVC
Pipe Size	Class 200 1"
Length	5 ft
Velocity	5 fps

**Recommendations**

Maximum Recommended Flow	13 gpm
Available Working Pressure	58.39 psi

**6001 CASSENA CV**

Design pressure all zones 65psi.



**JASON STUBBLEFIELD**  
9/23/2015

