

Maintenance Check List

,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Installation Completion Date: 10-28-15	
Address: 16717 Eider Ch	<i>(</i>
The following items have been provided an system owner or system owner's representation	nd explained to the irrigation
 The manufacturer's manual for the c A seasonal watering schedule. A list of components that require manufrequency of maintenance is attached. A permanent sticker has been attached warranty period for the irrigation system. The corrected or re-drawn design plainstallation and components of the system. Location and operation of the isolation. 	nintenance and the recommended d ed to the controller indicating the stem and contact information. ans indicating the actual ystem.
Irrigation system owner/representative	Date
This irrigation system has been installed in state and local laws, ordinances, rules, regu the system and determined that it has been irrigation plan and is properly adjusted for water at this time.	ulations or orders. I have tested installed according to the
JASON E STUBBLEFIELD	Irrigator/Date
N. PISTER SI	Irrigation Technician/ Date

Best of Texas

POBOX 776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Zone #	Description	Head Type	Run Time(Minutes)
1-2	b-ed	spray-bubb	let 10-12
3-6	turf	spray	25
7-12	turt	rotor	45

Month	Average	
	Cycles	
Jan.	3	
Feb.	3	
March	4	
April	4	
May	7	
June	9	
July	11	
Aug.	11	
Sept.	9	
Oct.	6	
Nov.	4	
Dec.	3	

MAINTENANCE ITEMS

Backflow device – Test Annually (Call Louis Sinclair 563-8762) Y-strainer – Check annually for debris

Heads - Run system monthly to check for leaks or broken nozzles

Valve covers – Trim grass around cover to expose

Controller - Check seasonally for correct run times

Winter - Run system briefly every 2 weeks if system remains in off position

Quantity	Symbol	Description	Part Number	Pressure	Flow	Radius
Sprinkler	S		1	rioudate	71011	rauius
3		Rain Bird 10F - 1804	10F	30 psi	1.58 gpm	10 ft
26	•	Rain Bird 10H - 1804	10H	30 psi	0.79 gpm	
22	•	Rain Bird 10Q	10Q	30 psi	0.39 gpm	
2	0	Rain Bird 1300A-F	1300AF	30 psi	1.7 gpm	0 ft
3		Rain Bird 5000-MPR-30-F - 5004-PL-FC	MPR-30-F	45 psi	5.78 gpm	30 ft
22 2 3 8	•	Rain Bird 5000-MPR-30-H - 5004-PL-PC		45 psi	2.96 gpm	30 ft
13	٠	Rain Bird 5000-MPR-30-Q - 5004-PL-PC	MPR-30-0	45 psi	1.4 gpm	30 ft
14	•	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	
11	•	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	
Meters/Pu	ımps			00 psi	o.zo gpiii	Oil
1	M					
Backflow	Devices					
1	8	Febco 715 - 1"	715 - 1"			
Control V	alves					
13	€	Rain Bird 100-DVF	100-DVF			
Y-Straine	rs / Filters	s	100 211			
1	-	Febco 650A-1"	4305			
Irrigation	Accessor	ries				
1	bd	Nelson 9501-100IN	9501-100IN			
1	A	Rain Bird E-4c	E-4c			
1	N	Rain Bird RSD-BEx	RSD-BEx			
Lateral Li	ne Pipe		NOD-DEX			
797 ft		Class 200 1"	0			
Mainline F	ipe		0			

Meter Size	5/8 inch meter	
Static Pressure	65 psi	
Elevation Change	0 ft	
Service Line Information		
Pipe Category	Class 200 PVC	
Pipe Size	Class 200 1*	
Length	5 ft	
Velocity	5 fps	
Recommendations		
Maximum Recommended Flow	13 gpm	
Available Working Pressure	58.39 psi	

16717 EIDER CV

Design pressure all zones 65psi.



JASON STUBBLEFIELD 10/28/2015



