

Maintenance Check List

Installation Completion Date: 10 29 15

Address: 3724 Lunet Ring Way

The following items have been provided and explained to the irrigation system owner or system owner's representative.

- · The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative

Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



Irrigator/Date

Irrigation Technician/ Date

Best of Texas

POBOX 776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Zone #	Description	Head Type	Run Time(Minutes)
1	bee	spray-bubb	let 10-12
2-4	turf	soray	25
5-6	torf	Potor	45
7	arass	drip	30
	D.		

Month	Average	
	Cycles	
Jan.	3	
Feb.	3	
March	4	
April	4	
May	7	
June	9	
July	11	
Aug.	11	
Sept.	9	
Oct.	6	
Nov.	4	
Dec.	3	

MAINTENANCE ITEMS

Backflow device – Test Annually (Call Louis Sinclair 563-8762)
Y-strainer – Check annually for debris
Heads – Run system monthly to check for leaks or broken nozzles
Valve covers – Trim grass around cover to expose
Controller – Check seasonally for correct run times

Winter - Run system briefly every 2 weeks if system remains in off position


Quantity	Symbol	Description	Part Number	Droceuro	Flow	Radius
Sprinkler		Description	rart Number	Pressure	Flow	Radius
1		Rain Bird 10F - 1804	405	100 1	11.00	
30	-	Rain Bird 10F - 1804	10F	30 psi	1.58 gpm	
19	•	Rain Bird 10H - 1804	10H	30 psi	0.79 gpm	
2	-	Rain Bird 5000-MPR-30-H - 5004-PL-PC	10Q	30 psi	0.39 gpm	
4		Rain Bird 5000-MPR-30-H - 5004-PL-PC	MPR-30-H	45 psi	2.96 gpm	
9		Rain Bird 8H - 1804		45 psi	1.4 gpm	30 ft
9		Rain Bird 8Q - 1804	8H	30 psi	0.52 gpm	
Meters/Pu		[Kdii] Diid 6Q - 1604	8Q	30 psi	0.26 gpm	8 ft
Metersift	imps			e.		
1	M					
Backflow						
1	0	Febco 715 - 1"	715 - 1"	1		
Control V	alves					
8	-	Rain Bird 100-DVF	100-DVF			
Y-Straine	rs / Filter		100-041			
1	-	Febco 650A-1"	4305			
Irrigation			4305			
1	>d	Nelson 9501-100IN				
1	A	Rain Bird E-4c	9501-100IN			
1	N N	Rain Bird RSD-BEx	E-4c			
		Rain Bird RSU-BEX	RSD-BEx			
Lateral Li	ne Pipe					
697 ft		Class 200 1"	0			
Mainline F	ipe					
227 ft		Class 200 1"	0			
Drip Tubir	ng					
97 ft		Rain Bird LD-09-12	LD-09-12			

3724 LUNET RING WAY

Design pressure all zones 65psi.



JASON STUBBLEFIELD 10/29/2015



Meter Size	5/8 inch meter		
Static Pressure	65 psi		
Elevation Change	0 ft		
Service Line Information			
Pipe Category	Class 200 PVC		
Pipe Size	Class 200 1"		
Length	5 ft		
Velocity	5 fps		
Recommendations			
Maximum Recommended Flow	13 gpm		
Available Working Pressure	58 39 nsi		

