

Maintenance Check List

Installation Completion Date: 11-25-15

Address: 6709 Davenport Divide

The following items have been provided and explained to the irrigation system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



Irrigator/Date

Irrigation Technician/ Date



POBOX 776 HUTTO, TX 78634

(512)228-4833 (512)852-9633 fax

Zone #	Description	Head Type	Run Time(Minutes)		
1-6	b-ed	Spray-bubbler 10-12			
7-10	turf	spraus	25		
11-15	torf	notors	45		

Month	Average		
	Cycles		
Jan.	3		
Feb.	3		
March	4		
April	4		
May	7		
June	9		
July	11		
Aug.	11		
Sept.	9		
Oct.	6		
Nov.	4		
Dec.	3		

MAINTENANCE ITEMS

Backflow device – Test Annually (Call Louis Sinclair 563-8762)
Y-strainer – Check annually for debris
Heads – Run system monthly to check for leaks or broken nozzles
Valve covers – Trim grass around cover to expose
Controller – Check seasonally for correct run times
Winter – Run system briefly every 2 weeks if system remains in off position

	Symbol	Description	Part Number	Dronning	Elem	D . 11
Sprinkler	s	200011711011	Fart Number	Pressure	Flow	Radius
29	•	Rain Bird 10H - 1804	10H	20!	0.70	10.0
17	•	Rain Bird 10Q	10Q	30 psi 30 psi		10 ft
7	0	Rain Bird 1300A-F	1300AF			10 ft
3		Rain Bird 5000-MPR-30-F - 5004-PL-FC	MPR-30-F	30 psi 45 psi	1.7 gpm	0 ft
5	•	Rain Bird 5000-MPR-30-H - 5004-PL-PC	MPR-30-H	45 psi	5.78 gpm	30 ft
11	•	Rain Bird 5000-MPR-30-Q - 5004-PL-PC	MPR-30-Q			30 ft
59	•	Rain Bird 8H - 1804	8H	45 psi	1.4 gpm	30 ft
39	•	Rain Bird 8Q - 1804	8Q	30 psi		8 ft
Meters/Pu	mps	1001	OQ	30 psi	0.26 gpm	8 11
1	M					
Backflow	Devices					
1	(lec)	Febco 715 - 1"	715 - 1"			
Control Va	alves		710-1			
16	€	Rain Bird 100-DVF	100-DVF			
Y-Strainer	s / Filters		TOU-DVF			
1	-	Febco 650A-1"	4305			
rrigation	Accessor	ries	4000			
1	M	Nelson 9501-100IN	9501-100IN			
1	Æ	Rain Bird ESP-4Me	ESP4ME		6709	DAV
1	N	Rain Bird RSD-BEx	RSD-BEx		3.00	
_ateral Lir	e Pipe		NOD-DEX	D	oolan -	
1507 ft		Class 200 1"	0	D	esign p	ressu
			U			
Mainline P	ipe					

Meter Size	5/8 inch meter		
Static Pressure	65 psi		
Elevation Change	0 ft		
Service Line Information			
Pipe Category	Class 200 PVC		
Pipe Size	Class 200 1"		
Length	5 ft		
Velocity	5 fps		
Recommendations			
Maximum Recommended Flow	13 gpm		
Available Working Pressure	58.39 psi		



Design pressure all zones 65psi.





JASON STUBBLEFIELD 11/25/2015



