

Maintenance Check List

Installation Completion Date: 12-9-15

Address: 7813 Turnback ledge

The following items have been provided and explained to the irrigation system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



Irrigator/Date

Irrigation Technician/ Date

## Best of Texas

POBOX 776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Zone #	Description	Head Type	Run Time(Minutes)
1	bed	Sprau-bub	bler 10-12
2-5	turf	Spray	25
6-8	turf	rotors	45
9	grass	anp	30

Month	Average	
	Cycles	
Jan.	3	
Feb.	3	
March	4	
April	4	
May	7	
June	9	
July	11	
Aug.	11	
Sept.	9	
Oct.	6	
Nov.	4	
Dec.	3	

## MAINTENANCE ITEMS

Backflow device - Test Annually (Call Louis Sinclair 563-8762)

Y-strainer - Check annually for debris

Heads - Run system monthly to check for leaks or broken nozzles

Valve covers - Trim grass around cover to expose

Controller - Check seasonally for correct run times

Winter - Run system briefly every 2 weeks if system remains in off position

Quantity	Symbol	Description				
Sprinkler	S	Description	Part Number	Pressure	Flow	Radius
32	•	Rain Bird 10H - 1804				
28	•	Rain Bird 100	10H	30 psi	0.79 gpm	10 ft
2		Rain Bird 5000 MDD 20 11 500 17	10Q	30 psi	0.39 gpm	10 ft
8	•	Rain Bird 5000-MPR-30-H - 5004-PL-PC Rain Bird 5000-MPR-30-Q - 5004-PL-PC		45 psi	2.96 gpm	30 ft
10	•	Rain Bird 8H - 1804		45 psi	1.4 gpm	30 ft
11	(*)	Rain Bird 8Q - 1804	8H	30 psi	0.52 gpm	
Meters/Pu	mns	real bird bQ - 1804	8Q	30 psi	0.26 gpm	8 ft
1 1	M					
Backflow	(0.00)					
1		E				
	8	Febco 715 - 1"	715 - 1"			
Control Va						
10	€	Rain Bird 100-DVF	100-DVF			
Y-Strainer	s / Filters		100-041			
1	-	Febco 650A-1"	4305			
Irrigation A	ccessor	ies	4305			
1		Nolson DEO4 400IN				
		Pain Pird FCD 484	9501-100IN			
		Pain Rind DCD DC.	ESP4ME			
ateral Lin	e Pipe	DIE NOD-DEX	RSD-BEx			
359 ft		Class 200 1"				
Mainline Pi		Ciass 200 I	0			
	-	Class 200 4#				
Orip Tubing		Class 200 1"	0			-
9 ft						(a
D IL	F	Rain Bird LD-09-12	D-09-12			

Water Source #1			
Meter Size	5/8 inch meter		
Static Pressure	65 psi		
Elevation Change	0 ft		
Service Line Information			
Pipe Category	Class 200 PVC		
Pipe Size	Class 200 1"		
Length	5 ft		
Velocity	5 fps		
Recommendations			
Maximum Recommended Flow	13 apm		
Available Working Pressure	58.39 psi		

## 7813 TURNBACK LEDGE

Design pressure all zones 65psi.





## JASON STUBBLEFIELD 12/9/2015



