

Maintenance Che	eck List
Installation Completion Date: 1-11-16	
Address: 229 Blue Waterly	eaf
The following items have been provided an system owner or system owner's representation	d explained to the irrigation tive.
 The manufacturer's manual for the co A seasonal watering schedule. A list of components that require mai frequency of maintenance is attached A permanent sticker has been attached warranty period for the irrigation syst The corrected or re-drawn design plan installation and components of the syst Location and operation of the isolation 	ntenance and the recommended d to the controller indicating the tem and contact information. ns indicating the actual stem.
Irrigation system owner/representative	Date
This irrigation system has been installed in a state and local laws, ordinances, rules, regulathe system and determined that it has been in irrigation plan and is properly adjusted for the water at this time.	ations or orders. I have tested
JASON E STUBBLEFIELD	Irrigation Technician/ Date

Best of Texas

POBOX 776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Zone#	Description	Head Type	Run Time(Minutes)
1	bed	spray-bubbler	10-12
2-4	Iturf	Sprays	25
5:-7	Iturf	hotors	45 "
8	larass	drip	30
	0		
****		i	y
	Trans.	(

Month	Average
	Cycles
Jan.	3
Feb.	3
March	4
April	4
May	7
June	9
July	11
Aug.	11
Sept.	9
Oct.	6
Nov.	4
Dec.	3

MAINTENANCE ITEMS

Backflow device - Test Annually (Call Louis Sinclair 563-8762)

Y-strainer - Check annually for debris

Heads - Run system monthly to check for leaks or broken nozzles

Valve covers - Trim grass around cover to expose

Controller - Check seasonally for correct run times

Winter - Run system briefly every 2 weeks if system remains in off position


Quantity	Symbol	Description	Part Number	Pressure	Flow	Radius
Sprinkle		Description	T LITE INCHINGO	110000110	11011	radius
20		Rain Bird 10H - 1804	10H	30 psi	0.79 gpm	10 ft
20	•	Rain Bird 10Q	10Q	30 psi		
1		Rain Bird 5000-MPR-30-F - 5004-PL-FC	MPR-30-F	45 psi	5.78 gpm	
2		Rain Bird 5000-MPR-30-H - 5004-PL-PC	MPR-30-H	45 psi	2.96 gpm	
9	•	Rain Bird 5000-MPR-30-Q - 5004-PL-PC		45 psi	1.4 gpm	30 ft
7	•	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	8 ft
12	•	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	
Meters/P	umps					
1	M	4		1		
Backflov	v Devices			•		
1	·	Febco 715 - 1"	715 - 1"	1		
Control '	Valves			*.		
9	•	Rain Bird 100-DVF	100-DVF	1		
Y-Strain	ers / Filter	S		1		
1	600	Febco 650A-1"	4305	1		
Irrigation	Accesso	ries				
1	M	Nelson 9501-100IN	9501-100IN	1		
1	A	Rain Bird ESP-4Me	ESP4ME	1		
1	N	Rain Bird RSD-BEx	RSD-BEx			
Lateral L	ine Pipe					
786 ft		Class 200 1"	0	1		1
Mainline	Pipe				5	
288 ft		Class 200 1"	0	1		
Drip Tub	ing					
84 ft		Rain Bird LD-09-12	LD-09-12	1		

229 BLUE WATERLEAF

Design presure all zones 65psi.



JASON STUBBLEFIELD 1/11/2016



Water Source #1		
Meter Size	5/8 inch meter	
Static Pressure	65 psi	
Elevation Change	0 ft	
Service Line Information		
Pipe Category	ory Class 200 PV0	
Pipe Size	Class 200 1"	
Length	5 ft	
Velocity	5 fps	
Recommendations		
Maximum Recommended Flow	13 gpm	
Available Working Pressure	58.39 psi	

