

Maintenanc	e Check List
Installation Completion Date: 2-2-2	2016
Address: 2509 yuma T	rail
The following items have been provid system owner or system owner's repre	
frequency of maintenance is attaA permanent sticker has been at	re maintenance and the recommended ached tached to the controller indicating the n system and contact information. In plans indicating the actual the system.
Irrigation system owner/representative	Date
This irrigation system has been installed state and local laws, ordinances, rules, the system and determined that it has been irrigation plan and is properly adjusted water at this time.	regulations or orders. I have tested been installed according to the
JASON E STUBBLEFIELD	Irrigation Technician/ Date



POBOX 776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Zone#	Description	Head Type	Run Time(Minutes)
	bed	spray-bubb	let 10-12
2-7	turf	Spraus	25
8-11	turf	notors	45
12	arass	drip	30
	V		
n.A. dr. Nr. sella s gare i del dilloce de ser se ser si autoriaris de seguidos consciolations qu			
inggy filological media, and filological filological photographs and a second second second second second second	The state of the s	BOAN MATERIAL STATE OF THE STAT	2
	E C	1,000	The state of the s

Month	Average
	Cycles
Jan.	3
Feb.	3
March	4
April	4
May	7
June	9
July	11
Aug.	11
Sept.	9
Oct.	6
Nov.	4
Dec.	3

MAINTENANCE ITEMS

Backflow device – Test Annually (Call Louis Sinclair 563-8762)
Y-strainer – Check annually for debris
Heads – Run system monthly to check for leaks or broken nozzles
Valve covers – Trim grass around cover to expose
Controller – Check seasonally for correct run times
Winter – Run system briefly every 2 weeks if system remains in off position


Quantity	Symbol	Description	Part Number	Pressure	Flow	Radius
Sprinkler	S					
4		Rain Bird 10F - 1804	10F	30 psi	1.58 gpm	10 ft
35	0	Rain Bird 10H - 1804	10H	30 psi	0.79 gpm	10 ft
41	•	Rain Bird 10Q	10Q	30 psi	0.39 gpm	
3	0	Rain Bird 1300A-F	1300AF	30 psi	1.7 gpm	0 ft
3	•	Rain Bird 5000-MPR-30-F - 5004-PL-FC	MPR-30-F	45 psi	5.78 gpm	
5	0	Rain Bird 5000-MPR-30-H - 5004-PL-PC		45 psi	2.96 gpm	
9	•	Rain Bird 5000-MPR-30-Q - 5004-PL-PC	MPR-30-Q	45 psi	1.4 gpm	30 ft
11	0	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	
13	0	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	8 ft
Meters/P	umps					
1	M					
Backflow	Devices		***************************************			
1	66	Febco 715 - 1"	715 - 1"			
Control V	alves					
13	•	Rain Bird 100-DVF	100-DVF			
Y-Straine	rs / Filter	\$	***************************************			
1	a	Febco 650A-1"	4305			
Irrigation	Accesso	ries				D
1	M	Nelson 9501-100IN	9501-100IN			D
1	A	Rain Bird ESP-4Me	ESP4ME			
1	1	Rain Bird RSD-BEx	RSD-BEx			
Lateral Li	ine Pipe	,				
943 ft	VARIABLE PRODUCTION AND ADDRESS OF THE PARTY	Class 200 1"	0			
Mainline	Pipe			-		
192 ft		Class 200 1"	0			
Drip Tubi	ng					
	1	Rain Bird LD-09-12	LD-09-12	1		

Irrigation

Meter Size	5/8 inch meter		
Static Pressure	65 psi		
Elevation Change	0 ft		
Service Line Information			
Pipe Category	Class 200 PV		
Pipe Size	Class 200 1"		
Length	5 ft		
Velocity	5 fps		
Recommendations			
Maximum Recommended Flow	13 gpm		
Available Working Pressure	58.39 psi		

2509 YUMA TRAIL

Design pressure all zones 65psi.





JASON STUBBLEFIELD 2/2/2016

