

## Maintenance Check List

Installation Completion Date: 2-13-10
Address: 3202 SKyndge
The following items have been provided and explained to t

system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



Irrigator/Date

Irrigation Technician/ Date



POBOX 776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Zone#	Description	Head Type	Run Time(Minutes)
1-2	bed	Sprau-bubb	der 10-12
3-s	turf	spraus	25
6-10	wrf	monors	465
-	arûss	dis	30
	I Y		A CONTRACTOR OF THE CONTRACTOR
		1	4-5-0000
			Additional or constraints

Month	Average
	Cycles
Jan.	3
Feb.	3
March	4
April	4
May	7
June	9
July	11
Aug.	11
Sept.	9
Oct.	6
Nov.	4
Dec.	3

## MAINTENANCE ITEMS

Backflow device - Test Annually (Call Louis Sinclair 563-8762)
Y-strainer - Check annually for debris
Heads - Run system monthly to check for leaks or broken nozzles
Valve covers - Trim grass around cover to expose
Controller - Check seasonally for correct run times
Winter - Run system briefly every 2 weeks if system remains in off position

rigation	Baratan -	Post Number 15	To Elaw De C	Water Source #1	
iantity   Symbol rinklers	Description	Part Number   Pressu	re Flow Radius	Meter Size	5/8 inch meter
•	Rain Bird 10F - 1804	10F 30 psi	1.58 gpm   10 ft	Static Pressure	65 psi
0	Rain Bird 10H - 1804 Rain Bird 10Q	10H 30 psi 10Q 30 psi	0.79 gpm   10 ft	Elevation Change	0 ft
0	Rain Bird 1300A-F	10Q 30 psi 1300AF 30 psi	0.39 gpm   10 ft   1.7 gpm   0 ft	Service Line Information	Class 200 PVC
•	Rain Bird 5000-MPR-30-F - 5004-PL	-FC MPR-30-F 45 psi	5.78 gpm   30 ft	Pipe Category Pipe Size	Class 200 PVC
0	Rain Bird 5000-MPR-30-H - 5004-PL	-PC MPR-30-H 45 psi	2.96 gpm 30 ft	Length	5 ft
•	Rain Bird 5000-MPR-30-Q - 5004-PL Rain Bird 8H - 1804	PC MPR-30-Q 45 psi 8H 30 psi	1.4 gpm   30 ft 0.52 gpm   8 ft	Velocity	5 fps
•	Rain Bird 8Q - 1804	8Q 30 psi	0.26 gpm   8 ft	Recommendations	
ters/Pumps				Maximum Recommended F	low 13 gpm
ckflow Devices				Available Working Pressure	58.39 psi
RIIOW Devices	Febco 715 - 1"	715 - 1"			
ntrol Valves	1 0000 1 10 1				
•	Rain Bird 100-DVF	100-DVF			
trainers / Filter					
	Febco 650A-1"	4305			
gation Accesso	Nelson 9501-100IN	9501-100IN			
<u>A</u>	Rain Bird ESP-4Me	ESP4ME			
. 8	Rain Bird RSD-BEx	RSD-BEx			
eral Line Pipe	4				
8 ft	Class 200 1"	0			
inline Pipe	Class 200 1"	0			
p Tubing	0/033 200 1				
ft	Rain Bird LD-09-12	LD-09-12			
00	202 SKY RIDGE LANE			_	
		Pos a f		1	
Des	ign pressure all zones 65	opsi.			
	S			9 1"	
	A			13.1 GPM	(10)
				ZONE 9	di di
					ZONE 1
7	M				ZUNE I
	TIZ PI		/		-
		(S		1"	1
		//	7 1"		
		//	ZONE 7 GPM	8 1"	1"
		H	7	7.16 GPM	
					F 0
				ZON	E 0
	V	17/	<b>•</b> !		
	1	/9			
	N	//	1 6		
		6	9!		•
		F			
	TE OFF TE	//	1-1		5 1"
	2 000000000000000000000000000000000000	//	1"		11.41 GPM
	0000000000000000000	//			ZONE
	JASON STUBBLEFIELD	//			2014
	12003	// (= ] = =			
	\$ 50 PB 4 10 P	// (6   1") GPM			
	SOURCE THE PROPERTY OF THE PRO				
		// ZONE 6			
		J" 1"			
		6			
			7.42		
			ZOI	NE 1	
JAS	ON STUBBLEFIE	ILU 🎾		ZONE 2 2 1"	
			G 11,	ZONE Z	
2/13	/2016	No.		1" GPM	7
				· ·	11
			ZONE 3		· 🖟 🐈
			11.04	1 <b>T</b>	
		Ĭ	11.04 GPM	1	
ī	·		1	H-1-0	
			11 - 17	1 d	
			(C)	TO A	
	40 00	40	· ·	11	
0	10 20	40		n GP	1"
0	10 20 1" = 20'	40		1 1	1" M

1" = 20'