

Maintenance Check List

Installation Completion Date: 10-19-16

Address: 8708 cattle Baron tath


The following items have been provided and explained to the irrigation system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative

10-19-19 Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



| 10|19|2010 | Irrigator/Date

Irrigation Technician/ Date

Best of Texas Landscapes

POBOX776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Description	Head Type	Run Time(Minutes)	
bed	spray-bubbler	10-12	
turf	sprays	25	
gruss	anp	30	
19			
	Description bed Furf gruss	bed spray-bubbler turf sprays	

Month	Average
	Cycles
Jan.	3
Feb.	3
March	4
April	4
May	7
June	9
July	11
Aug.	11
Sept.	9
Oct.	6
Nov.	4
Dec.	3

MAINTENANCE ITEMS


Backflow device – Test Annually (Call Louis Sinclair 563-8762)
Y-strainer – Check annually for debris
Heads – Run system monthly to check for leaks or broken nozzles
Valve covers – Trim grass around cover to expose
Controller – Check seasonally for correct run times
Winter – Run system briefly every 2 weeks if system remains in off position

Irrigati	on					
Quantity	Symbol	Description	Part Number	Pressure	Flow	Radius
Sprinkler	S					
	•	Rain Bird 10F - 1804	10F	30 psi	1.58 gpm	
3 27	0	Rain Bird 10H - 1804	10H	30 psi	0.79 gpm	10 ft
13	•	Rain Bird 10Q	10Q	30 psi	0.39 gpm	
49	•	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	
50	. 🔿	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	8 ft
Meters/Pu	umps					
1	M					
Backflow	Devices					
1	66	Febco 715 - 1"	715 - 1"]		
Control V	alves					
10	•	Rain Bird 100-DVF	100-DVF			
Y-Straine	rs / Filter	S				
1	CID CID	Febco 650A-1"	4305			
Irrigation	Accesso	ries		8	708 C	AIII
1	M	Nelson 9501-100IN	9501-100IN]	D	
1	<u>A</u>	Rain Bird ESP-4Me	ESP4ME]	Design	pressu
1		Rain Bird RSD-BEx	RSD-BEx			
Lateral Li	ne Pipe					
1291 ft		Class 200 1"	0			
Mainline	Pipe					
259 ft		Class 200 1"	0			
Drip Tubi	ng	9				
187 ft		Rain Bird LD-09-12	LD-09-12			
	1			_		

Water Source #1	F/0 : 1 t		
Meter Size	5/8 inch meter		
Static Pressure	65 psi		
Elevation Change	0 ft		
Service Line Information			
Pipe Category	Class 200 PVC		
Pipe Size	Class 200 1"		
Length	5 ft		
Velocity	5 fps		
Recommendations			
Maximum Recommended Flow	13 gpm		
Available Working Pressure	58.39 psi		

8708 CATTLE BARON PATH

Design pressure all zones 65psi.





JASON STUBBLEFIELD 10/19/2016

