

Maintenance Check List

Installatio	n Comp	letion Da	te: [-22-1	6	
Address:	105	AXIS	Lap		


The following items have been provided and explained to the irrigation system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative

11-22-16 Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



Irrigator/Date

Irrigation Technician/ Date



POBOX 776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Zone #	Description	Head Type	Run Time(Minutes)
1-6	Bed	SDYLLY-bubbl	
7-11	ITURF	soraus	25
12-15	TURE	votors	45
10	Gruss	Dhip	30

Month	Average
	Cycles
Jan.	3
Feb.	3
March	4
April	4
May	7
June	9
July	11
Aug.	11
Sept.	9
Oct.	6
Nov.	4
Dec.	3

MAINTENANCE ITEMS

Backflow device – Test Annually (Call Louis Sinclair 563-8762)
Y-strainer – Check annually for debris
Heads – Run system monthly to check for leaks or broken nozzles
Valve covers – Trim grass around cover to expose
Controller – Check seasonally for correct run times
Winter – Run system briefly every 2 weeks if system remains in off position

Quantity	Symbol	Description	Part Number	Pressure	Flow	Radius
Sprinkler			Table 2000 and government of the second	hanna and a said a	J. 21-2-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	
3	•	Rain Bird 10F - 1804	10F	30 psi	1.58 gpm	10 ft
39	•	Rain Bird 10H - 1804	10H	30 psi	0.79 gpm	
29	0	Rain Bird 10Q	10Q	30 psi	0.39 gpm	
29 5 3 8	0	Rain Bird 1300A-F	1300AF	30 psi	1.7 gpm	0 ft
3	0	Rain Bird 5000-MPR-30-H - 5004-PL-PC	MPR-30-H	45 psi	2.96 gpm	30 ft
8	•	Rain Bird 5000-MPR-30-Q - 5004-PL-PC	MPR-30-Q	45 psi	1.4 gpm	30 ft
1	•	Rain Bird 8F - 1804	8F	30 psi	1.05 gpm	8 ft
57	0	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	
48	0	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	8 ft
Meters/Pu	imps					
1	M			1		
Backflow	Devices			•		
1	@	Conbraco 4A-205-T2	4A-205-T2			
Control V	alves					
17	@	Rain Bird 100-DVF	100-DVF			
Y-Straine	rs / Filter	S				
1	623	Febco 650A-1"	4305			
Irrigation	Accesso	ries	Annual photo angular and a survey of a sur			
1	M	Nelson 9501-100IN	9501-100IN			
1	A	Rain Bird ESP-4Me	ESP4ME			
1	9	Rain Bird RSD-BEx	RSD-BEx			
Lateral Li	ne Pipe			•		
1308 ft		Class 200 1"	0	1		
Mainline I	Pipe		A	•		
242 ft		Class 200 1"	0			
Drip Tubi	30	1	I	1		
99 ft	.a	Rain Bird LD-09-12	LD-09-12	7		

Water Source #1	
Meter Size	5/8 inch meter
Static Pressure	65 psi
Elevation Change	0 ft
Service Line Information	1
Pipe Category	Class 200 PVC
Pipe Size	Class 200 1"
Length	5 ft
	5 fps

Maximum Recommended Flow 13 gpm Available Working Pressure 58.39 psi

	-			
		N		
		1		
		A		
		II.		
		11		
		11		
		1 1		
		18		
	/	AR		
	1%	y NX	\	
	1/\		//	

Design pressure all zones 65psi.

105 AXIS LOOP



Jason Stubblefield 11|22|2016

