

Maintenance Check List


Installatio	on Completi	ion Date:	12-15-16	
Address:	9005	Bays	share	

The following items have been provided and explained to the irrigation system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



| 12 | 15 | 20 | U

Irrigation Technician/ Date

Best of Texas Landscapes

POBOX776 HUTTO, TX78634 (512)228-4833 (512)852-9633 fax

Zone#	Description	Head Type	Run Time(Minutes)
1	Bed	spray-bub	10-12
2-5	TUTE	Koraus	25
0	arass	dip	30
	O'	, ,	
			1

Month	Average
	Cycles
Jan.	3
Feb.	3
March	4
April	4
May	7
June	9
July	11
Aug.	11
Sept.	9
Oct.	6
Nov.	4
Dec.	3

MAINTENANCE ITEMS

Backflow device – Test Annually (Call Louis Sinclair 563-8762)
Y-strainer – Check annually for debris
Heads – Run system monthly to check for leaks or broken nozzles
Valve covers – Trim grass around cover to expose
Controller – Check seasonally for correct run times
Winter – Run system briefly every 2 weeks if system remains in off position

indegr	on					
Quantity		Description	Part Number	Pressure	Flow	Radius
Sprinkler					La tanana and a same	
4		Rain Bird 10F - 1804	10F	30 psi	1.58 gpm	10 ft
23	0	Rain Bird 10H - 1804	10H	30 psi		10 ft
21	0	Rain Bird 10Q	10Q	30 psi	0.39 gpm	10 ft
2	0	Rain Bird 1300A-F	1300AF	30 psi	1.7 gpm	0 ft
4	•	Rain Bird 5000-MPR-30-Q - 5004-PL-PC	MPR-30-Q	45 psi	1.4 gpm	30 ft
7	0	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	8 ft
13	0	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	8 ft
Meters/Pr	umps					
1	M			1		
Backflow	Devices			1		
1	(e)	Conbraco 4A-205-T2	4A-205-T2]		
Control V	/alves			-		
7	0	Rain Bird 100-DVF	100-DVF]		
Y-Straine	rs / Filter	S		-		
1	610	Febco 650A-1"	4305	1		
Irrigation	Accesso	ries		-		
1	M	Nelson 9501-100IN	9501-100IN]		
1	A	Rain Bird ESP-4Me	ESP4ME	1		
1	1	Rain Bird RSD-BEx	RSD-BEx			
Lateral Li	ine Pipe			-		
818 ft	T	Class 200 1"	0]		
Mainline	Pipe			-		
150 ft		Class 200 1"	10	1		

Water Source #1			
Meter Size	5/8 inch meter		
Static Pressure	65 psi		
Elevation Change	0 ft		
Service Line Information			
Pipe Category	Class 200 PVC		
Pipe Size	Class 200 1"		
Length	5 ft		
Velocity	5 fps		
Recommendations			
Maximum Recommended Flow	13 gpm		
Available Working Pressure	58.39 psi		

9005 BAYSHORE

Design pressure all zones 65psi.





Jason Stubblefield 12|15|2016

