

Maintenance Check List


Installatio	n Com	pletion Da	te: <u>2-3-1</u>	1	
Address:	101	ratie	Orive		

The following items have been provided and explained to the irrigation system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



2/3/2017 Irrigator/Date

Irrigation Technician/ Date

## Best of Texas Landscapes

POBOX 776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Zone#	Description	Head Type	Run Time(Minutes)
1-2	Bed	Head Type Spray-bub	10-12
3-6	turf	sprays	25
7-10	turf	rotors	45
			4
	-	es e	

Month	Average
	Cycles
Jan.	3
Feb.	3
March	4
April	4
May	7
June	9
July	11
Aug.	11
Sept.	9
Oct.	6
Nov.	4
Dec.	3

## MAINTENANCE ITEMS

Backflow device – Test Annually (Call Louis Sinclair 563-8762)
Y-strainer – Check annually for debris
Heads – Run system monthly to check for leaks or broken nozzles
Valve covers – Trim grass around cover to expose
Controller – Check seasonally for correct run times
Winter – Run system briefly every 2 weeks if system remains in off position

Irrigati	on		*				
Quantity	Symbol	Description	Part Number	Pressure	Flow	Radius	
Sprinkler	Sprinklers						
1	•	Rain Bird 10F - 1804	10F	30 psi	1.58 gpm	10 ft	
35	0	Rain Bird 10H - 1804	10H	30 psi	0.79 gpm		
24	0	Rain Bird 10Q	10Q	30 psi	0.39 gpm	10 ft	
3	0	Rain Bird 1300A-F	1300AF	30 psi	1.7 gpm	0 ft	
3	•	Rain Bird 5000-MPR-30-F - 5004-PL-FC	MPR-30-F	45 psi	5.78 gpm	30 ft	
3 6 8	0	Rain Bird 5000-MPR-30-H - 5004-PL-PC	MPR-30-H	45 psi	2.96 gpm	30 ft	
	٥	Rain Bird 5000-MPR-30-Q - 5004-PL-PC	MPR-30-Q	45 psi	1.4 gpm	30 ft	
18	•	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	8 ft	
20	0	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	8 ft	
Meters/Pu	Meters/Pumps						
1	M						
Backflow	Devices			•			
1	<u>@</u>	Conbraco 4A-205-T2	4A-205-T2				
Control V	Control Valves						
11	0	Rain Bird 100-DVF	100-DVF				
Y-Strainers / Filters							
1	<b>a</b>	Febco 650A-1"	4305				
Irrigation Accessories							
1	M	Nelson 9501-100IN	9501-100IN				
1	Æ	Rain Bird ESP-4Me	ESP4ME				
1		Rain Bird RSD-BEx	RSD-BEx	2 2 2			
Lateral Line Pipe							
906 ft	-	Class 200 1"	0				
Mainline Pipe							
251 ft		Class 200 1"	0				

Water Source #1	T - 12
Meter Size	5/8 inch meter
Static Pressure	65 psi
Elevation Change	0 ft
Service Line Information	
Pipe Category Pipe Size	Class 200 PVC Class 200 1"

500000	Recommendations	
	Maximum Recommended Flow	13 gpm
		58.39 psi

## **161 KATIE DRIVE**

Design pressure all zones 65psi.





Jason Stubblefield 2/3/2017

