

Maintenance Check List

Installation	Completion	Date:/	-30-17

Address: 406 wynpage Drive


The following items have been provided and explained to the irrigation system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative

1-30-17 Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



1/30/2017 Irrigator/Date

Irrigation Technician/ Date

Best of Texas Landscapes

POBOX 776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Bed	Head Type SPYCH-LAB	10-12
turf	COMMILS	75
	Suluy	23
torf	rotors	45
	10/1	turt roturs

Month	Average		
	Cycles		
Jan.	3		
Feb.	3		
March	4		
April	4		
May	7		
June	9		
July	11		
Aug.	11		
Sept.	9		
Oct.	6		
Nov.	4		
Dec.	3		

MAINTENANCE ITEMS

Backflow device – Test Annually (Call Louis Sinclair 563-8762)
Y-strainer – Check annually for debris
Heads – Run system monthly to check for leaks or broken nozzles
Valve covers – Trim grass around cover to expose
Controller – Check seasonally for correct run times
Winter – Run system briefly every 2 weeks if system remains in off position

Irrigati	on					
Quantity	Symbol	Description	Part Number	Pressure	Flow	Radius
Sprinkler	S		•			
5	•	Rain Bird 10F - 1804	10F	30 psi	1.58 gpm	10 ft
26	0	Rain Bird 10H - 1804	10H	30 psi	0.79 gpm	10 ft
24	0	Rain Bird 10Q	10Q	30 psi	0.39 gpm	10 ft
2	0	Rain Bird 1300A-F	1300AF	30 psi	1.7 gpm	0 ft
1	•	Rain Bird 5000-MPR-30-F - 5004-PL-FC	MPR-30-F	45 psi	5.78 gpm	30 ft
5	0	Rain Bird 5000-MPR-30-H - 5004-PL-PC	MPR-30-H	45 psi	2.96 gpm	
9	٥	Rain Bird 5000-MPR-30-Q - 5004-PL-PC	MPR-30-Q	45 psi	1.4 gpm	30 ft
18	•	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	8 ft
17	0	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	8 ft
Meters/Pu	umps					
1	M			1		
Backflow	Devices		******	τ.		
1	(ec)	Conbraco 4A-205-T2	4A-205-T2			
Control V	alves					
11	•	Rain Bird 100-DVF	100-DVF]		
Y-Straine	rs / Filter	S		•		
1	a	Febco 650A-1"	4305			
Irrigation	Accesso	ries				
1	M	Nelson 9501-100IN	9501-100IN	1		
1	A	Rain Bird ESP-4Me	ESP4ME			
1		Rain Bird RSD-BEx	RSD-BEx			
Lateral Li	ne Pipe					
951 ft		Class 200 1"	0			
Mainline	Pipe					
235 ft		Class 200 1"	0	1		

Nater Source #1	TE/0: -1	
Meter Size	5/8 inch meter	
Static Pressure	65 psi	
Elevation Change	e 0 ft	
Service Line Information	n .	
Pipe Category	Class 200 PVC	
Pipe Size	Class 200 1"	
	5 ft	
Length		

Maximum Recommended Flow 13 gpm Available Working Pressure 58.39 psi

406 WYNNPAGE DR

Design pressure all zones 65psi.





Jason Stubblefield 1|30|2017

