

Maintenance Check List

Installatio	on Com	pletion Da	te: 2-23-1	17
Address:	517	San	Miche	lle


The following items have been provided and explained to the irrigation system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative

2-23-[7 Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



| 2 | 2 3 | 2 0 | 7 | | Irrigator/Date

Irrigation Technician/ Date

## Best of Texas Landscapes

POBOX 776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Zone#	Description	Head Type	Run Time(Minutes)
1-2	Bed	spray-bub	10-12
3-6	nrf	sprays	25
7-	etooss	dirip	30
	9 5		
			,

Month	Average
	Cycles
Jan.	3
Feb.	3
March	4
April	4
May	7
June	9
July	11
Aug.	11
Sept.	9
Oct.	6
Nov.	4
Dec.	3

## MAINTENANCE ITEMS

Backflow device – Test Annually (Call Louis Sinclair 563-8762)
Y-strainer – Check annually for debris
Heads – Run system monthly to check for leaks or broken nozzles
Valve covers – Trim grass around cover to expose
Controller – Check seasonally for correct run times
Winter – Run system briefly every 2 weeks if system remains in off position

Irrigat	ion		•			
Quantity	Symbol	Description	Part Number	Pressure	Flow	Radius
Sprinkler						
5		Rain Bird 10F - 1804	10F	30 psi	1.58 gpm	10 ft
24	0	Rain Bird 10H - 1804	10H	30 psi	0.79 gpm	
24 28 2 5 2 26	0	Rain Bird 10Q	10Q	30 psi	0.39 gpm	
2	0	Rain Bird 1300A-F	1300AF	30 psi	1.7 gpm	0 ft
5	•	Rain Bird 5000-MPR-30-Q - 5004-PL-PC	MPR-30-Q	45 psi	1.4 gpm	30 ft
2	•	Rain Bird 8F - 1804	8F	30 psi	1.05 gpm	
26	0	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	
22	0	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	8 ft
Meters/P	umps		,			
1	M			1		
Backflow	Devices					
1	<u>©</u>	Conbraco 4A-205-T2	4A-205-T2	]		
Control \	/alves					
8	•	Rain Bird 100-DVF	100-DVF	]		
Y-Straine	ers / Filter	S				
1	<b>GD</b>	Febco 650A-1"	4305	1		
Irrigation	Accesso	ries		-		
1	M	Nelson 9501-100IN	9501-100IN	1		
1	A	Rain Bird ESP-4Me	ESP4ME			
1		Rain Bird RSD-BEx	RSD-BEx			
Lateral L	ine Pipe					
1005 ft	T	Class 200 1"	0	1		
Mainline	Pipe	4		=		
171 ft		Class 200 1"	0	1		

Water Source #1	
Meter Size	5/8 inch meter
Static Pressure	65 psi
Elevation Change	0 ft
Service Line Information	n
Pipe Category	Class 200 PVC
Pipe Size	Class 200 1"
Length	5 ft
Velocity	5 fps

Recommendations	
Maximum Recommended Flow	13 gpm
	58.39 psi

## **517 SAN MICHELLE CV** Design pressure all zones 65psi.





Jason Stubblefield 2|23|2017

