

Maintenance Check List

Installation	Completion	Date:	4-4-17

Address: 3032 DESERT Shoule


The following items have been provided and explained to the irrigation system owner or system owner's representative.

- The manufacturer's manual for the controller.
- A seasonal watering schedule.
- A list of components that require maintenance and the recommended frequency of maintenance is attached
- A permanent sticker has been attached to the controller indicating the warranty period for the irrigation system and contact information.
- The corrected or re-drawn design plans indicating the actual installation and components of the system.
- Location and operation of the isolation valve.

Irrigation system owner/representative

<u>4-4-17</u> Date

This irrigation system has been installed in accordance with all applicable state and local laws, ordinances, rules, regulations or orders. I have tested the system and determined that it has been installed according to the irrigation plan and is properly adjusted for the most efficient application of water at this time.



4/4/2017 Irrigator/Date

Irrigation Technician/ Date

Best of Texas Landscapes

POBOX 776 HUTTO, TX 78634 (512)228-4833 (512)852-9633 fax

Zone#	Description	Head Type	Run Time(Minutes)	
1-2	turf	rotors	45	
ì	rurf	rotors	42	
2-3	Bed	sprays	25	
4	anuss	drip	30	
	V			
			A	
	inscience			

Month	Average
l l	Cycles
Jan.	3
Feb.	3
March	4
April	4
May	7
June	9
July	11
Aug.	11
Sept.	9
Oct.	6
Nov.	4
Dec.	3

MAINTENANCE ITEMS

Backflow device – Test Annually (Call Louis Sinclair 563-8762)
Y-strainer – Check annually for debris
Heads – Run system monthly to check for leaks or broken nozzles
Valve covers – Trim grass around cover to expose
Controller – Check seasonally for correct run times
Winter – Run system briefly every 2 weeks if system remains in off position

7 7						
Irrigat	ion					
Quantity	Symbol	Description	Part Number	Pressure	Flow	Radius
Sprinkle	rs		•		Annual Congruence	
27	. •	Rain Bird 10H - 1804	10H	30 psi	0.79 gpm	10 ft
4	•	Rain Bird 10Q	10Q	30 psi	0.39 gpm	
4 2 7		Rain Bird 5000-MPR-30-F - 5004-PL-FC		45 psi	5.78 gpm	
7	0	Rain Bird 5000-MPR-30-H - 5004-PL-PC	MPR-30-H	45 psi	2.96 gpm	
5	•	Rain Bird 5000-MPR-30-Q - 5004-PL-PC	MPR-30-Q	45 psi	1.4 gpm	30 ft
	0	Rain Bird 8H - 1804	8H	30 psi	0.52 gpm	8 ft
4	0	Rain Bird 8Q - 1804	8Q	30 psi	0.26 gpm	
Meters/P	umps					
1	M			1		
Backflow	/ Devices	9		,		
1	@	Conbraco 4A-205-T2	4A-205-T2	1		
Control Valves				τ.		
7	•	Rain Bird 100-DVF	100-DVF			
Y-Straine	ers / Filter	S				
1	65	Febco 650A-1"	4305	I		
Irrigation	Accesso	ries				
1	M	Nelson 9501-100IN	9501-100IN			
2	A	Rain Bird ESP-4Me	ESP4ME			
2		Rain Bird RSD-BEx	RSD-BEx			
Lateral L	ine Pipe			'		
810 ft	of the transmission of the second	Class 200 1"	0			
Mainline	Pipe					
85 ft		Class 200 1"	0			
Drip Tubing						
138 ft		Rain Bird LD-09-12	LD-09-12			

Water Source #1		
Meter Size	5/8 inch meter	
Static Pressure	65 psi	
Elevation Change	0 ft	
Service Line Information		
Pipe Category	Class 200 PVC	
Pipe Size	Class 200 1"	
Length	5 ft	
Velocity	5 fps	
Recommendations		
Maximum Recommended Flow	13 gpm	
Available Working Pressure	58.39 psi	

3032 DESERT SHADE Design pressure all zones 65psi.





Jason Stubbefield 4|4|2017

