Texas Commission on Environmental Quality
BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

	-	
í	ROH	80
	ad other	

	ompleted for each assemb	ly tested. A sign	ed and dated	l original must be submitte	d to the public water supplier	for recordkeeping *purposes:			
NAME OF PWS:									
PWS ID#:	DDEGG.			S					
PWS MAILING ADI	· · · · · · · · · · · · · · · · · · ·								
PWS CONTACT PE		Lake Stone	Dr	· Parameter and the second					
				ested and maintaine	ed as required by comp	nission regulations			
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters.									
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):									
Reduced Press	sure Principle (RPF		Reduced Pressure Principle-Detector (RPBA-D)						
	Valve (DCVA)		Double Check-Detector (DCVA-D)						
	um Breaker (PVB)		Spill-Resistant Pressure Vacuum Breaker (SVB)						
		<u>' </u>	opin re						
	pollo			Size:	1"				
	P4A			BPA Location:	Residential Landscape Irrigation				
Serial Number:	932735			BPA Serves:	Residential Landscap	e irrigation			
Reason for test: New 🗵 Existing 🗆 Replacement 🗆 Old Model/Serial #									
Is the assembly instal	led in accordance v	with manufa	cturer red	commendations and	d/or local codes?	Yes □ No			
Is the assembly instal	led on a non-potab	le water sup	ply (auxi	liary)?		☐ Yes 🖾 No			
TEST RESULT	Reduced Pressure	Principle A	ssembly	(RPBA)	PVE	B & SVB			
PASS 🔀		DCVA							
FAIL	1st Check			Relief Valve	Air Inlet	Check Valve			
		psid Held atpsid		Opened of	d Opened at	Held at psid			
Initial Test				Opened at psi					
Date: 292419		t Closed Tight		Did not open		Leaked			
Time: 1100AH	Leaked 🗀	Leaked			Did not open				
					Did it fully open				
					(Yes □ /No □)				
D : 136 : 1					(105 Li into Li)				
Repairs and Materials Used**									
Osed									
Test After Repair	Held at psid		1	Opened at psi	1 -	Held at psid			
Date:	Closed Tight	Closed Tig	ght 🗆		psid				
Time:									
*** 2 nd check: numeric reading required for DCVA only									
Differential pressure gauge used: Potable: Non-Potable: □									
Make/Model: Midwest / 845-3 SN: 06111314 Date tested for accuracy: 04/29/19									
Remarks: None									
AVAILABLE TOTAL									
Company Name: L Sinclair Services Inc. Licensed Tester				ed Tester Name	Lewis R. S	Sinclair			
Company Ivame.		(Print/7		ACCOUNT OF THE PARTY OF THE PAR					
	L Silician Servi		(Print/T	ype):	3	4 6			
Company Address:	Cedar Park, TX			Type): ed Tester Name (Sig	gnature).	2 July			
Company Address: Company Phone #:			License BPAT I	ed Tester Name (Sig License #	BP0002815	المأشلج			
	Cedar Park, TX		License BPAT I	d Tester Name (Sig		2 Julas			

The above is certified to be true at the time of testing.

^{*} TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)]

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS