## Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form mu		ich assembly tested. A sign				for recordkeeping *purposes:	
NAME OF PWS:		Dripping Springs WSC					
PWS ID#:		1050013					
PWS MAILING	101 Hays St ste 40	6 Dripping Sprin	igs, TX 78620				
		Tracy Gray					
			Ridge Dripping Springs 78620				
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations							
and is certified to be operating within acceptable parameters.							
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):							
						21	
Double Check Valve (DCVA)			Double Check-Detector (DCVA-D) Type II				
Pressure Vacuum Breaker (PVB)Spill-Resistant Pressure Vacuum Breaker (SVB)							
Manufacturer: Main: Febco Bypa					<b>1</b>		
Model Number: Main: 850		Bypass:		BPA Location:		Right front yard 5 feet from meter	
Serial Number: Main HF72426 By			pass: BPA Serves: Irrigation				
Reason for test:	New 🛛 🛛	Existing	Replacement	Old Model/Seri	al #		
Is the assembly installed in accordance with manufacturer recommendations and/or local codes? $\square$ Yes $\square$ No							
Is the assembly	installed on a no	n-potable water sup	ply (auxiliary)?			$\Box$ Yes $\boxtimes$ No	
TEST RESULT		1 1		TracII			
IESI KESULI	Reduced Press	re Principle Assem	$h_{\rm W}$ (RPRA)	Type II Assembly	PVB & SVB		
[]	Reduced Tresse	ite i filicipie Assein	$\Pi (\mathbf{K}^{F}\mathbf{D}\mathbf{A})$	Assembly			
PASS 🖾 🛛		DCVA	Daliaf Value	Drugon Choole	A : T 1 4	Chaola Value	
FAIL	1 <sup>st</sup> Check	2 <sup>nd</sup> Check***	Relief Valve	Bypass Check	Air Inlet	Check Valve	
Initial Test	Held at 2.3 psic	Held at 2.4 psid	Opened at	Held at psid	Opened at	psid Held at	
Date: 6/7/2021	Closed Tight 🛛	Closed Tight	psid	Closed Tight	Did not open	□ psid	
Time:	Leaked	Leaked	Did not	Leaked	Did it fully oper	n Leaked 🛛	
11:15AM	I	1 1 1	open 🔲		(Yes 🛛 /No 🗆		
Repairs and Main:							
Materials							
Used**	Bypass:						
Test After	Held at psi	d Held at psid	Opened at	Held at psid	Opened at	psid Held at	
<u>Repair</u>	Closed Tight	Closed Tight	psid	Closed		psid	
Date:	- 1	,		Tight 🗖			
Time:				х э.			
*** 2 <sup>nd</sup> check: numeric reading required for DCVA only							
Differential pressure gauge used:					Non-Potable:		
Make/Model:	MidWest 845	SN:	10150482	Date tes	sted for accurac	ey: 10/9/2020	
Remarks:							
Company Name: Safewater Backflow		Backflow	Licensed Tester Name Brad Weyant (Print/Type):		ant		
Company Address: PO Box		002 Austin,TX	Licensed Tester Neme (Signature):				
1 2	78765		Licensed Tester Name (Signature).				
Company Phone #: 512-0		790	BPAT License # BP0016935				
			License Expirat				
The above is certified to be true at the time of testing.							

\* TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)] \*\* USE ONLY MANUFACTURER'S REPLACEMENT PARTS