Texas Commission on Environmental Quality

BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping *purposes						r for recordkeeping *purposes:	
NAME OF PWS:		Dripping Springs WSC					
PWS ID#:		1050013					
PWS MAILING ADDRESS:		101 Hays St. Ste. 406 Dripping Springs, TX 78620					
		Tracy Gray 1390 Pink Granite Blvd. Dripping Springs, TX 787620					
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations							
and is certified to be operating within acceptable parameters.							
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):							
☐ Reduced	☐ Reduced Pressure Principle (RPBA) ☐ Reduced Pressure Principle-Detector (RPBA-D) Type II ☐						
_	heck Valve (DC	, , , , , , , , , , , , , , , , , , ,					
Pressure Vacuum Breaker (PVB) Spill-Resistant Pressure Vacuum Breaker (SVB)							
Manufacturer: Main: Febco Bypass: Size: Main: 1" Bypass:						Bypass:	
Model Number: Main: 850		Bypass:		BPA Location:	Right front yard 5 ft from meter		
Serial Number: Main: HF84576		Bypass:		BPA Serves:	Irrigation		
Reason for test: New 🗵 Existing 🔲 Replacement 🗀 Old Model/Serial #							
Is the assembly installed in accordance with manufacturer recommendations and/or local codes?							
						☐ Yes ☐ No	
		- potable water suppl	(uummary):	Т. н			
TEST RESULT	Dadwaad Praggy	ra Drinainla Agamh	l _{vr} (DDD A)	Type II	PVB & SVB		
[]	Reduced Flessi	re Principle Assemb	y (RPDA)	Assembly	PVB & SVB		
PASS 🖾	Γ	OCVA	Dalia CValera	D	A in Lulus		
	1 st Check 2 nd Check***		Relief Valve	Bypass Check	Air Inlet	Check Valve	
Initial Test	Held at 2.0 psid	Held at 2.0 psid	Opened at		Opened at	psid Held at	
Date:	Closed Tight	Closed Tight	psid	Closed Tight	Did not	psid	
12/28/2021	Leaked \square	Leaked	Did not	LCaked	open Did it Leaked D		
Time: 10:45AM			open L		fully open (Yes	s 🔲 📗	
					/No 🔲)		
Repairs and	Main:						
Materials							
Used**	Bypass:						
Test After	Held at psi	d Held at psid	Opened at	Held at psid	Opened at	psid Held at	
Repair	Closed Tight [Closed Tight	psid	Closed	-	psid	
Date:				Tight \square			
Time:							
*** 2 nd check: numeric reading required for DCVA only							
Differential pressure gauge used: Potable: Non-Potable: □							
Make/Model: MidWest 845 SN: 10150482 Date tested for accuracy: 10/7/2021							
Remarks:							
Company Name: Safewater I				Licensed Tester Name (Print/Type): Brad Weyant			
Company Address: PO Box 4		02 Austin, TX 78765	5 Licensed Te	Licensed Tester Name (Signature):			
Common Plane # 512 (05 0700 DRATE) # DROOT (025							
Company Phone #: 512-60							
			License Exp	oration Date: 12	2/3/2024		

The above is certified to be true at the time of testing.

^{*} TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)]

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS