CLWSC - Triple Peak - Backflow Prevention Assembly Test and Maintenance Report

The following form must be completed for each assembly tested for recordkeeping *purposes:

	CLWSC - Triple Peak P.O. Box 1742	PWS ID: Contact Name:	0460172
	Canyon Lake, Texas 78133	Phone Number	: 830-312-4600
		BPAT Information	
Company Name: Tester Name: Address:	Safewater Backflow and Irrigation Brad Weyant 609 E 50TH AUSTIN, Texas 78751	n Phone Number Email Address License Numbe License Expira	brad@safewateratx.com BP0016935
	Location Information		Contact Information
Property Type: Business Name: Property Address:	Residential 1542 Escarpment New Braunfels, TX 78132	Company Nam Contact Name: Mailing Addres Phone Number Email Address	s: 1542 Escarpment New Braunfels, TX 78132
		Backflow Information	
The backflow prevention acceptable parameters.	assembly detailed below has been	tested and maintained as required by co	mmission regulations and is certified to be operating within
Backflow Method: Main Assembly Manufa Location: Hazard Type ****:	Double Check Valve acturer: Febco Left front yard 5 feet from meter Irrigation - Non Chemical	Model: 850 Size:	1 Serial Number: HF58738
Backflow Test Information			
Test Result: Reason for Test:	Passed New Installation		
Is the assembly installe	ed in accordance with manufactu	rers recommendations and/or local co	des? Yes
Is the assembly installed on a non-potable water supply (auxiliary)? No			
Differential pressure gauge used:	Midwest 845-5 (potable)	Serial Number: 10150482	Date Tested for Accuracy: 10/7/2021
5	Do	uble Check Valve	1
	Check Valve #1	Check Valve #2	
Initial Test Date: 3/18/2022 Time: 2:30 PM	Held at 1.9 PSID ClosedTight Leaked	Held at 1.9 PSID ✔ ClosedTight ☐ Leaked	
Repairs and Materials Used			
Repair Details		· · ·]
Test After Repai	rs Held at 0 PSID	Held at 0 PSID	
		Remarks	-

The above is certified to be true at the time of testing. * TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC 290.46(B)] ** USE ONLY MANUFACTURER'S REPLACEMENT PARTS *** 2nd Check: Numeric reading required for double check valve only. **** Indicates additional information not present on the standard TCEQ report