pfluTexas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

| The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping "purple" | | | | | | | nukceping purposes. | | | |
|--|--|------------------------------|--------------------------------------|----------------------|---|----------------------------|---------------------|------------------------------------|-----------|--|
| NAME OF PWS: | | | | Pflugerville Water | | | | | | |
| PWS ID#: | | | 2270014 | | | | | | | |
| | | ADDRESS: | 100 E Main St Pflugerville, TX 78660 | | | | | | | |
| PWS 0 | CONTAC | Γ PERSON: | Backflow I | Backflow Inspections | | | | | | |
| ADDRESS OF SERVICE: 1600 Carvin Way Pflugerville, TX 78660 | | | | | | | | | | |
| The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations | | | | | | | | | | |
| and is certified to be operating within acceptable parameters. | | | | | | | | | | |
| TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA): | | | | | | | | | | |
| | ☐ Reduced Pressure Principle (RPBA) ☐ Reduced Pressure Principle-Detector (RPBA-D) Type II ☐ | | | | | | | | | |
| ☐ Double Check Valve (DC | | | CVA) | | Double Check-Detector (DCVA-D) Type II | | | | | |
| ☐ Pressure Vacuum Breaker (PVB) ☐ Spill-Resistant Pressure Vacuum Breaker (SVB) | | | | | | | • • • | | | |
| | | | | | | | | | | |
| | facturer: | Main: Apollo | | Bypas | | Size: | | Main: 1" Bypass: | | |
| | l Number: | 1 | | Bypass: | | BPA Location | | Right front yard 5 feet from meter | | |
| Serial Number: | | Main 53622C Bypass: | | ass: | BPA Serves: | | Irrigation | Irrigation | | |
| | | | | | | | | | | |
| Reason for test: New ⊠ Existing □ Replacement □ Old Model/Serial # | | | | | | | | | | |
| Tree E Existing I represented I of the Wood Serial " | | | | | | | | | | |
| • | | | | | | | | | | |
| Is the assembly installed on a no | | | on-potable wa | ter supp | oly (auxiliary)? | | | | Yes No | |
| TEST RESULT Redu | | | | | | Type II | | | | |
| | | Reduced Pres | sure Principle | Assemb | ly (RPBA) | Assembly | P | PVB & SVB | | |
| | ~~ 5] | | | | 1 | , | 1 | | | |
| PASS ⊠ FAIL □ | | DCVA 1st Check 2nd Check*** | | | Relief Valve | Bypass Check | Air Inlet | Air Inlet | | |
| | | | | | | Dypass Check | All fillet | | | |
| Initial ' | Test | Held at 1.6 p | sid Held at 1. | 4 psid | Opened at | Held at psic | Opened at | psid | Held at | |
| | | Closed Tight | _ | | psid | Closed Tight | Did not open | | psid | |
| Date: 12/5/2023 Time: 12:15PM | | | | | Did not | _ _ | · | d it fully open Lea | | |
| | | Leaked Leaked | | | open 🔲 | Leaked \square | (Yes /No | 1 | Leaked | |
| | | | | | 1 [] | | (i es 🗀 /No L | | | |
| | pairs and Main: | | | | | | | | | |
| Materials Used** | | | | | | | | | | |
| | | Bypass: | | | | | | | | |
| Test A | fter | Held at p | sid Held at | nsid | Opened at | Held at psic | Opened at | nsid | Held at | |
| Repair | | Closed Tight | 1 | | psi | Closed | opened at | _ рыа | psid | |
| Date: | 1 | Closed Tight | Closed 11 | | Por | Tight \square | | | Poru | |
| Time: | | | | | | | | | | |
| 1 11110. | I | *** 2nd -11 | | lina | wined for DCVA | omly, | | | <u> </u> | |
| D:cc | 4:.1 . | | | ınıg req | uired for DCVA | • | | | | |
| Differential pressure gauge used: | | | _ | Potable: 2 | Non-Potable: | | | | | |
| Make/Model: MidWest 845 | | | SN: | 10150482 | ested for accurac | ed for accuracy: 10/4/2023 | | | | |
| Remarks: | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| Company Name: Safewater Backflow | | | | | Licensed Tester Name Brad Weyant | | | | | |
| | | | | | (Print/Type): | | | | | |
| Company Addre | | PO Box 4002 Austin, TX 78765 | | ΓX | Licensed Tester Name (Signature): | | | | | |
| Company Phone | | | | | BPAT License # BP0016935 | | | | | |
| S12-003-7/70 | | | | | License Expiration Date: 12/3/2024 | | | | | |
| The above is certified to be true at the time of testing. | | | | | | | | | | |
| | | | THE SIMPLE | | | | | | | |

^{*} TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)]
** USE ONLY MANUFACTURER'S REPLACEMENT PARTS