Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping *purposes:										
	E OF PWS	S:	WTCPUA							
			2270235							
		ADDRESS:		13215 Bee Cave Pkwy Building B Suite 110 Bee Caves, TX 7738						
PWS CONTACT PERSON: WTCPUA B										
ADDRESS OF SERVICE: 401 Old Stone Rd. Austin, TX 78738										
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters.										
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):										
	Reduced	Pressure Principle (RPBA) Reduced Pressure Principle-Detector (RPBA-D) Type II								
	Double Check Valve (DCVA) □ Double Check Valve (DCVA)			+	Double Check-Detector (DCVA-D) Type II					
☐ Pressure Vacuum Breaker					Spill-Resistant Pressure Vacuum Breaker (SVB)					
Manufacturer: Main: Apollo Bypass: Size: Main: 1"								Bypass:		
Model Number:		Main:DC4A		Bypass:	[]	BPA Location	71 0			
Serial Number:		,		/pass:		BPA Serves:	Irrigation			
DIA Serves. Integration										
Reason for test: New ⊠ Existing □ Replacement □ Old Model/Serial #										
Is the assembly installed in accordance with manufacturer recommendations and/or local codes?									Yes No	
Is the assembly installed on a non-potable water su					ply (auxiliary)?				Yes 🛮 No	
				- 11		T II			1 10 1 - 110	
PASS ⊠ FAIL □		D . 1 1 D	D.:	A1.	1 (DDD A)	Type II	, n	PVB & SVB		
		Reduced Press	ure Principle A	Assemb	Iy (KPBA)	Assembly	Р			
			DCVA							
		1st Check	2 nd Check	***	Relief Valve	Bypass Check	Air Inlet		Check Valve	
			1 11 11 4 .			TT 11	1 0 1			
Initial '		Held at _1.8psi	T	[]	Opened at psid	î	Opened at	T 1	Held at	
Date: 12/6/2023 Time: 12:15PM		Closed Tight \	† II	nt 🔼	Did not	Closed Tight	Did not open			
		Leaked Leaked			open	Leaked	Did it fully ope	1		
							(Yes □ /No □	Ц /No Ц)		
Repairs	and	Main:								
Materia										
Used**		Bypass:								
Test After Repair Date:		Held at ps	id Held at	psid	Opened at	Held at psid	d Opened at	psid	Held at	
		Closed Tight Closed Tigh			psid	Closed	1	1	psid	
				,	1	Tight □				
Time:	1					11gm _				
*** 2 nd check: numeric reading required for DCVA only										
Differential pressure gauge used:				<u> </u>	Potable: 2	Non-Potable:				
Make/Model: MidWest 845 SN:			SN:	10150482	ested for accurac	ey:	10/4/2023			
Remarks:										
Compa	any Name	Safewater Backflow			Licensed Tester Name Brad Weyant					
		78765			(Print/Type): Licensed Tester Name (Signature):					
Compa	any Addre									
Compa	any Phone	<i>‡</i> : 512-605-9790		_	BPAT License # BP0016935					
License Expiration Date: 12/3/2024										
			The charge:	a aautif	ad to be turned	t the time of tes	tina			

The above is certified to be true at the time of testing.
* TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)]
** USE ONLY MANUFACTURER'S REPLACEMENT PARTS