Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping *purposes:

NAME OF PWS:

Dripping Springs WSC

NAM	E OF PWS	:	Dripping Springs WSC						
PWS ID#:			1050013						
PWS MAILING ADDRESS:			101 Hays St. Ste. 406 Dripping Springs, TX 78620						
PWS	CONTAC	Γ PERSON:	Cory Taylor						
ADDRESS OF SERVICE: 384 Comfort Maple Ln. Dripping Springs, TX 787620									
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations									
and is certified to be operating within acceptable parameters.									
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):									
☐ Reduced Pressure Principle			ole (RPBA) ☐ Reduced Pressure Principle-Detector (RPBA-D) Type II ☐						
		,	, <u> </u>		Double Check-Detector (DCVA-D) Type II □				
	Pressure	Vacuum Break	er (PVB)		Spill-Resistant	pill-Resistant Pressure Vacuum Breaker (SVB)			
Manu	facturer:	Main: Apollo		Bypas	SS:	Size: Main: 1" Bypass:			
Model Number:				Bypass:		BPA Location:	Left front yard 5 feet from meter		
Serial Number:		Main: 53509C		Bypass		BPA Serves:	Irrigation		
Schar Number. Main. 33307C Bypass. BITT Serves. Inigation									
Reason for test: New X Existing Replacement Old Model/Serial #									
The Landing La								D	
Is the assembly installed in accordance with manufacturer recommendations and/or local codes? \(\text{Yes} \) \(\text{No} \) Is the assembly installed on a non-potable water supply (auxiliary)? \(\text{Yes} \) \(\text{No} \)									
Is the	assembly	installed on a n	on-potable v	water su	apply (auxiliary	7)?		☐ Yes No	
TEST	RESULT					Type II			
		Reduced Press	ure Principle	e Assen	nbly (RPBA)	Assembly	PVB & SVB		
PASS ⊠]	3			
		DCVA			Relief Valve	Bypass Check	Air Inlet	Check Valve	
FAIL 🗆		1 st Check 2 nd Check***							
<u>Initial Test</u>		Held at 1.9 psid	Held at _2	.0 psid	Opened at	Held at psid		_psid Held at	
Date: 2/14/2024 Time: 11:20AM		Closed Tight 🛛 Closed Tight 🖾			psid	Closed Tight Did not		psid	
		Leaked [Leaked		Did not	Leaked \square	open Did i	it Leaked \square	
				_	open \square		fully open (Ye	es 🔲 📗	
							/No □)		
D :	1	N /					/110	<u> </u>	
Repair		Main:							
Materi		Dymagg							
Used** Bypass:									
Test A		Held at ps					Opened at	_psid Held at	
<u>Repair</u>		Closed Tight	Closed Ti	ight \square	psid	Closed		psid	
Date:						Tight □			
Time:								<u></u>	
*** 2 nd check: numeric reading required for DCVA only									
Differential pressure gauge used: Potable: ☑ Non-Potable: ☐									
Make/Model:MidWest 845SN:10150482Date tested for accuracy:10/4/2023									
Remarks:									
Company Name: Safewater Backflow Licensed Tester Name (Print/Type): Brad Weyant									
_	oany Name					Licensed Tester Name (Print/Type): Brad Weyant Licensed Tester Name (Signature):			
Comp	any Addie	88. FO DOX 4002 AUSUII, 1A /8/03			Dicenseu 1	Licensed Tester Ivalite (Signature).			
Company Phone #: 512-605-9790 BPAT License # BP0016935						6025			
1 7									
License Expiration Date: 12/3/2024 The shows is cortified to be true at the time of testing									

The above is certified to be true at the time of testing.

^{*} TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)]

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS