Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping *purposes:

NAME OF PWS:				Round Rock Water								
PWS ID#:				2460003								
PWS MAILING ADDRESS:			3400 Sunrise Rd Round Rock, TX 78665									
PWS CONTACT PERSON:				Inspections 1816 Sawmill Xing Round Rock, TX 78681								
	RESS OF											
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations												
and is certified to be operating within acceptable parameters.												
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA): Reduced Pressure Principle (RPBA) Reduced Pressure Principle-Detector (RPBA-D) Type II												
·					Reduced Pressure Principle-Detector (RPBA-D) Type II							
			neck Valve (DCVA)			Double Check-Detector (DCVA-D) Type II						
	Pressure	Vac	uum Breake	r (PVB)		Spill-Resistant Pressure Vacuum Breaker (SVB)						
Manu	facturer:	M	ain: Apollo		Bypas	ss: Size: Main: 1" Bypass:						
Model Number				Bypas				tion:	Left front yard 5 feet from meter			
Serial Number:		M	Main 83230C		Bypass:		BPA Serve	es:	Irrigation			
·												
Reason for test: New ⊠ Existing □ Replacement □ Old Model/Serial #												
Trem E Existing E Treplacement E old Model Serial "												
Is the assembly installed in accordance with manufacturer recommendations and/or local codes? $\boxtimes Y_{es} \square N_{o}$												
Is the assembly installed on a non-potable water supply (auxiliary)?									Yes No			
TEST	RESULT						Type II					
		Reduced Pressure Principle Asser				nbly (RPBA)	Assembly		PVB & SVB		SVB	
PASS ⊠		DCVA]						
						Relief Valve	Bypass Check		Air Inlet		Check Valve	
FAIL			1 st Check 2 nd Ch		<***							
Initial Test Date: 5/21/2024 Time: 3:30PM		Held at 2.0 psid Held at _1. Closed Tight ⊠ psid			9	psid	II — <u>-</u> II		Opened at psid Held at Did not open		Held at	
											psid	
		Leal	ced \square	Closed Tigh	t 🛛	Did not	Leaked \square		id it fully open Leaked		Leaked	
				Leaked \square		open \square	_		Yes □ /No □)			
Donair	e and	Mai	Main:									
Repairs and Materials		iviani.										
Used**		Bypass:										
Test After Repair Date:		Held at psid Held at Closed Tight □ Closed Tig					Held at psid Closed Tight		Opened at psid		Held at	
					ght \square						psid	
Time:												
Tillic.		**	k Ond 1 1	<u> </u>	1.	. 16 DG	X 7 A 1					
*** 2 nd check: numeric reading required for DCVA only Differential pressure gauge used: Potable: Non-Potable:												
_				~~~				Non-Potable:		0 // 1/2 0 0 1		
Make/Model: Mid West 845 SN: 09231317 Date tested for accuracy: 3/14/20										3/14/2024		
Remarks: Permit#												
1 CIAITE!												
Comp	any Nam	e:	Safewater	Backflow		Licensed Tester Name			Brad Wey	ant		
Jomp		Sare water Buention				(Print/Type):						
Company Addr		ess:	PO Box 40	002 Austin, TX		Licensed Tester Name (Signature):						
			78765	,								
Company Phone		e #: 512-605-9790				BPAT License # BP0016935						
P	J = -1011					License Expiration Date: 12/3/2024						
						License Lapitation Date. 12/3/2027						

The above is certified to be true at the time of testing.

^{*} TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)]

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS