City of Georgetown - Backflow Prevention Assembly Test and Maintenance Report

The following form must b	e completed for each assembly teste	ed for recordkeeping *purposes:			
	City of Georgetown PO Box 1430 Georgetown, Texas 78626	PWS ID: Contact Nam Phone Numb	,		
BPAT Information					
Company Name: Tester Name: Address:	L Sinclair Services, Inc. Lewis Sinclair 1307 Machado Road Cedar Park, Texas 78613	Phone Numb Email Addre License Num License Exp	lss@austin.rr.com hber: BP0002815		
Location Information Contact Information				mation	
Property Type: Business Name: Property Address:	Residential 208 Spence Ln Liberty Hill, TX 78642	Company Na Contact Nam Mailing Addr Phone Numb Email Addres	ress: 208 Spence Ln Liberty Hill, TX 786	208 Spence Ln Liberty Hill, TX 78642	
Backflow Information					
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters.					
Backflow Method: Reduced Pressure Principle Main Assembly Manufacturer: Apollo Model: RP4A Size: 1 Serial Number: 38118C Location: 8' SW of meter					
Hazard Type ****: Irrigation - Non Chemical					
Backflow Test Information					
Test Result: Passed Reason for Test: New Installation					
Is the assembly installed in accordance with manufacturers recommendations and/or local codes? Yes					
Is the assembly installed on a non-potable water supply (auxiliary)? No Differential pressure Bac-Flo Bac-Flo 3 (potable) Serial Number: 03162474 Date Tested for Accuracy: 3/16/2023 gauge used:					
Reduced Pressure Principle					
	Check Valve #1	Check Valve #2	Relief Valve		
Initial Test Date: 8/23/2023 Time: 2:20 PM	Held at 7.9 PSID ☑ ClosedTight ☐ Leaked	Held at 0 PSID ✓ ClosedTight Leaked	Opened at 4.8 PSID Did not open		
Repairs and Materials Used					
Repair Details					
Test After Repairs	Held at 0 PSID	Held at 0 PSID Closed Tight	Opened at 0 PSID		
		Remarks			

The above is certified to be true at the time of testing.

* TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC 290.46(B)]

** USE ONLY MANUFACTURER'S REPLACEMENT PARTS

*** 2nd Check: Numeric reading required for double check valve only.

**** Indicates additional information not present on the standard TCEQ report