## Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping \*purposes:

NAME OF PWS:

Dripping Springs WSC

NAME OF PWS:		5:	Dripping Springs WSC						
PWS ID#:			1050013						
PWS MAILING ADDRESS:			101 Hays St. Ste. 406 Dripping Springs, TX 78620						
		Γ PERSON:	Cory Taylor						
ADDRESS OF SERVICE: 287 Kings Pine Dr. Dripping Springs, TX 787620									
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations									
and is certified to be operating within acceptable parameters.									
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):									
☐ Reduced Pressure Princ			The deced Tressure Timespie Detector (Id Bit D)						
		Check Valve (DCVA)			Double Check-Detector (DCVA-D) Type II $\Box$				
	Pressure	Vacuum Break	er (PVB)		Spill-Resistant Pressure Vacuum Breaker (SVB)				
Manu	facturer:	Main: Apollo	Main: Apollo B		ass: Size: Main: 1" Bypass:			Bypass:	
Model Number:		-		Bypass:		BPA Location:	* *		
Serial Number:		Main: 82474C		Bypass		BPA Serves:	Irrigation		
Reason for test: New ⊠ Existing □ Replacement □ Old Model/Serial #									
							⊠ Yes □ No		
Is the assembly installed on a non-potable water supply (auxiliary)?									
TECT DECLI T									
TEST RESULT		Reduced Pressure Principle Assembl			-lalar (DDD A)	Type II	D	ND 0- CMD	
		Reduced Piess	ure Principie	Assen	ibiy (KPDA)	Assembly	PVB & SVB		
PASS 🗵		DCVA			D 1: CX/ 1	D CI 1	A * T 1 .		
FAIL		1st Check 2nd Check***			Relief Valve	Bypass Check	Air Inlet	<sup>I</sup> Check Valve	
<b>Initial Test</b>		Held at 2.3 psid	d at 2.3 psid Held at _2.1 psid C			Held at psid	Opened at psid Held at		
Date: 5/17/2024 Time: 5:00PM		Closed Tight \	II	ht 🛛	psid	Closed Tight $\Box$	Did not psid psid Leaked □		
		Leaked [	_		Did not	Leaked $\square$			
		Leaked	Leaked		open $\square$		fully open (Ye	$_{\mathrm{s}}$ $\square$	
							/No □)	~ —	
D :	1	N /			<u> </u>		/110 <b>L</b> )	<u> </u>	
Repairs and Materials		Main:							
		Dymagay							
Used** Bypass:									
Test A		Held at ps	id Held at	psid			Opened at	_psid Held at	
<u>Repair</u>		Closed Tight [	Closed Ti	ight $\square$	psid	Closed		psid	
Date:						Tight $\square$			
Time:									
*** 2 <sup>nd</sup> check: numeric reading required for DCVA only									
Differential pressure gauge used: Potable: ☐ Non-Potable: ☐									
Make/Model:MidWest 845SN:09231317Date tested for accuracy:3/4/2024									
Remarks:									
Company Name:   Safewater Backflow   Licensed Tester Name (Print/Type):   Brad Weyant									
	any Addre					Licensed Tester Name (Signature):			
151									
Company Phone #: 512-605-9790					BPAT Lice	BPAT License # BP0016935			
License Expiration Date: 12/3/2024									
The above is certified to be true at the time of testing									

<sup>\*</sup> TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)]

<sup>\*\*</sup> USE ONLY MANUFACTURER'S REPLACEMENT PARTS