Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping *purposes:

NAME OF PWS:		Aqua Water Supply Corporation					
PWS ID#:		110013					
PWS MAILING ADDRESS:		415 Old Austin Hwy., Bastrop, TX 78602					
PWS CONTACT PERSON:		Chuck Kellogg					
ADDRESS OF SERVICE:		133 Booted Eagle Claw Cv. Cedar Creek, TX 78612					
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations							
and is certified		within acceptable					
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):							
☒ Reduced Pressure Principle (RPBA)			Reduced Pressure Principle-Detector (RPBA-D) Type II				
☐ Double Check Valve (DCVA)		CVA)	Double Check-Detector (DCVA-D) Type II □				
☐ Pressure Vacuum Breaker (PVB) ☐ Spill-Resistant Pressure Vacuum Breaker (SVB)							
			ss: Size: Main: 1" Bypass:				
Model Number:	Model Number: Main: 860		s:	BPA Location: Right front side of driveway at m BPA Serves: Irrigation		de of driveway at meter	
Serial Number: Main HA30192		2 Bypass:	Bypass:		Irrigation		
Reason for test: New ⊠ Existing □ Replacement ⊠ Old Model/Serial #							
Is the assembly installed in accordance with manufacturer recommendations and/or local codes?							
Is the assembly installed on a non-potable water supply (auxiliary)? ☐ Yes ☐ No							
TEST RESULT				Type II			
ILSI KLSCLI		ure Principle Asse	embly (RPBA)	Assembly	PVB & SVB		
-		<u> </u>		,			
PASS ⊠		OCVA	Relief Valve	Bypass Check	Air Inlet	Check Valve	
FAIL 🗆	1st Check	2 nd Check***					
<u>Initial Test</u>	Held at 7.2	Held at psi		Held at psid	Opened at	_psid Held at	
Date: 5/31/2024	psid	Closed Tight	3.4 psid	Closed Tight	Did not open	psid	
Time: 1:25PM	Closed Tight 🛛	Leaked	Did not	Leaked \Box	Did it fully open	Leaked \square	
	Leaked [open \square	Beaked	(Yes □ /No □		
Panaire and	Main	<u> </u>			<u> ` </u>	<u>′</u>	
Repairs and Main: Materials							
Used**	Dymogg.						
	Bypass:	1					
Test After		d Held at psi		_	Opened at	_psid Held at	
Repair	Closed Tight	Closed Tight	J∥ ^{psia}	Closed		psid	
Date:				Tight \square			
Time:	<u> </u>	. 1.	. 16 56	X 7 A 1			
*** 2 nd check: numeric reading required for DCVA only Differential pressure gauge used: Potable: Non-Potable:							
			Potable: Data to		Non-Potable: Stad for accuracy: 2/14/2024		
Make/Model: MidWest 845 SN: 09231317 Date tested for accuracy: 3/14/2024							
Remarks:							
Company Name: Safewater		Backflow		Licensed Tester Name (Print/Type): Brad Weyant			
Company Addre	ess: PO Box 4002 Austin,TX 78765		(Print/Type): Licensed Tester Name (Signature):				
Company Audio			Licensed Tester Ivallie (Signature).				
Company Dham		700	BPAT License # BP0016935				
Company Phone #: 512-605-9790 BPAT License # BP0016935 License Expiration Date: 12/3/2024							
The above is certified to be true at the time of testing							

^{*} TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)]

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS