## Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping \*purposes:

NAME OF PWS:		Round Rock Water							
PWS ID#:		2460003							
PWS MAILING		3400 Sunrise Rd Round Rock, TX 78665							
PWS CONTAC	Inspections								
ADDRESS OF SERVICE: 1809 Settlers Glen Dr. Round Rock, TX 78681									
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations									
and is certified to be operating within acceptable parameters.									
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):  Reduced Pressure Principle (RPBA) Reduced Pressure Principle-Detector (RPBA-D) Type II									
		1 ,	Ш	Reduced Pressure Principle-Detector (RPBA-D)  Type II					
☑   Double Check Valve (DCVA)				Double Check-Detector (DCVA-D) Type II □					
☐ Pressure Vacuum Breaker (PVB) ☐ Spill-Resistant Pressure Vacuum Breaker (SVB)									
Manufacturer:	anufacturer: Main: Apollo Bypa				ass: Size: Main: 1" Bypass:				
Model Number: Main: DC4A		Bypas		ss: BPA Locatio		ation:	Right front yard 10 feet from meter		
Serial Number: Main 83460C		]	Bypass:		BPA Serves:		Irrigation		
Reason for test: New ☑ Existing □ Replacement □ Old Model/Serial #									
Is the assembly installed in accordance with manufacturer recommendations and/or local codes?   Yes   No									
TEST RESULT					Type II				
	Reduced Pressure Principle Assem			ibly (RPBA)	Assembly		PVB & SVB		
PASS 🖾									
		1		Relief Valve	Bypass Check		Air Inlet	Check Valve	
FAIL 🗆	1st Check	2 <sup>nd</sup> Chec	K*** 						
<b>Initial Test</b>	Held at 2.2 psid Closed Tight ☐ Held at _2.1_ psid Closed Tight ☐ Closed Tight ☐			Opened at			pened at psid Held at id not open		
Date: 5/29/2024				psid					
Time: 3:15PM	Leaked [	Leaked		Did not	Leaked $\square$		d it fully open Leaked [		
				open $\square$			/es □ /No □ )		
Repairs and									
Materials Wall.									
Used**	Bypass:								
TD 4 64									
		_					pened at	_psid Held at	
Repair Date:	Closed Tight [	∐Closed Tig	ght $\square$	-	Closed			psid	
Time:					Tight $\square$				
Time.	*** 2nd 1 1		.41	1 . DC	X7.A 1.			<u> </u>	
*** 2 <sup>nd</sup> check: numeric reading required for DCVA only  Differential pressure gauge used:  Potable:  Non-Potable:									
1 0 0			CNI.				Non-Potable:  def or accuracy: 3/14/2024		
Make/Model:	09231317 Date tested for accuracy:   3/14/2024								
Remarks: Permit#									
Company Name: Safewater Backflow				Licensed Tester Name Brad Weyant					
G		002 1		(Print/Type):					
Company Addre				Licensed Tester Name (Signature):					
78765						/ <b>~</b>			
Company Phone #: 512-605-9790 BPAT License # BP0016935									
License Expiration Date: 12/3/2024  The shave is contified to be true at the time of testing									

The above is certified to be true at the time of testing.

<sup>\*</sup> TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC  $\S290.46(B)$ ]

<sup>\*\*</sup> USE ONLY MANUFACTURER'S REPLACEMENT PARTS