Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping *purposes:

NAME OF PWS:

Dripping Springs WSC

NAME OF PWS:		5 :	Dripping Springs WSC						
PWS ID#:			1050013						
PWS MAILING ADDRESS:			101 Hays St. Ste. 406 Dripping Springs, TX 78620						
		Γ PERSON:	Cory Taylor						
ADDRESS OF SERVICE: 395 Comfort Maple Ln. Dripping Springs, TX 787620									
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations									
and is certified to be operating within acceptable parameters.									
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):									
☐ Reduced Pressure Princi			Treduced Tressare Timespie Detector (Id Dif D)				O) Type II □		
		theck Valve (DCVA)			Double Check-Detector (DCVA-D) Type II \square				
	Pressure	Vacuum Break	er (PVB)		Spill-Resistant	pill-Resistant Pressure Vacuum Breaker (SVB)			
Manu	facturer:	Main: Apollo	ollo		pass: Size: Main: 1" Bypass:				
Model Number:		Main: DC4A		Bypass:		BPA Location:	* *		
Serial Number:		Main: 82546C		Bypass		BPA Serves:	Irrigation		
Reason for test: New ⊠ Existing □ Replacement □ Old Model/Serial #									
							⊠ Yes □ No		
Is the assembly installed on a non-potable water supply (auxiliary)? ☐ Yes ☐ No									
								_ 105 _ 110	
TEST RESULT		Reduced Pressure Principle Assembl			alalar (DDD A)	Type II	D	ND 0- CMD	
		Reduced Piess	ure Principle	Assen	ibly (KPDA)	Assembly	PVB & SVB		
PASS 🖾		DCVA			D II CAA I	D C1 1	A * T 1 .		
FAIL 🗆		1st Check 2nd Check***			Relief Valve'	Bypass Check	Air Inlet	^I Check Valve	
Initial Test		Held at 2.0 psid	t 2.0 psid Held at _2.1 psid C			Held at psid	Opened at psid Held at		
Date: 5/31/2024		Closed Tight 🛛 Closed Tight 💆		-	Opened at psid	Closed Tight			
Time: 10:40AM		Leaked [_		Did not	Leaked \square	open Did it Leaked D		
		Leakeu L	Leakeu	ш	open \square		fully open (Ye	s 🗆 📗	
							/No [])		
D :	1	3.6 .					/140 LL)		
Repairs and Materials		Main:							
		P							
Used** Bypass:									
Test A	<u> After</u>	Held at ps	id Held at	psid	_		Opened at	_psid Held at	
Repair		Closed Tight [☐ Closed Ti	ight \square	psid	Closed		psid	
Date:						Tight □			
Time:									
*** 2 nd check: numeric reading required for DCVA only									
Differential pressure gauge used: Potable: Non-Potable: □									
Make/Model:MidWest 845SN:09231317Date tested for accuracy:3/4/2024							cy: 3/4/2024		
Remarks:									
Company Name: Safewater Backflow Licensed Tester Name (Print/Type): Brad Weyant									
	any Addre					Licensed Tester Name (Signature):			
Company Phone #: 512-605-9790 BPAT License # BP0016935									
License Expiration Date: 12/3/2024									
The above is certified to be true at the time of testing									

^{*} TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)]

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS