City of Kyle - Backflow Prevention Assembly Test and Maintenance Report

The following form must be completed for each assembly tested for recordkeeping *purposes:

City of Kyle		**PWS ID:**	1050002
520 E RR 150		**Contact Name:**	Mickal Morrison
Kyle, Texas 78640		**Phone Number:**	737-877-2927

BPAT Information

Company Name:	Safewater Backflow and Irrigation	**Phone Number:**	5126059790
Tester Name:	Brad Weyant	**Email Address:**	brad@safewateratx.com
Address:	609 E 50TH	**License Number:**	BP0016935
	AUSTIN, Texas 78751	**License Expiration:**	12/3/2024

Location Information / Contact Information

Property Type:	Residential	**Company Name:**	
Business Name:		**Contact Name:**	
Property Address:	449 Jackson River Loop	**Mailing Address:**	449 Jackson River Loop
	Kyle, TX 78640		Kyle, TX 78640
		Phone Number:	
		Email Address:	

Backflow Information

The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters.

Backflow Method:	Double Check Valve						
Main Assembly Manufacturer:	Apollo	**Model:**	DC4A	**Size:**	1	**Serial Number:**	94120C
Location:	Left front yard 5 feet from meter						
Hazard Type ****:	Irrigation - Non Chemical						

Backflow Test Information

Test Result:	Passed
Reason for Test:	New Installation

Is the assembly installed in accordance with manufacturers recommendations and/or local codes? Yes

Is the assembly installed on a non-potable water supply (auxiliary)?   No

Differential pressure gauge used:	MidWest 845-5 (potable)	**Serial Number:**	09231317	**Date Tested for Accuracy:**	3/14/2024

	Double Check Valve	
	Check Valve #1	**Check Valve #2**
Initial Test **Date: 10/8/2024** **Time: 10:50 AM**	Held at 2 PSID ☑ ClosedTight ☐ Leaked	Held at 2.1 PSID ☑ ClosedTight ☐ Leaked
Repairs and Materials Used		
Repair Details		
Test After Repairs	Held at 0 PSID ☐ Closed Tight	Held at 0 PSID ☐ Closed Tight

Remarks

The above is certified to be true at the time of testing.
* TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC 290.46(B)]
** USE ONLY MANUFACTURER'S REPLACEMENT PARTS
*** 2nd Check: Numeric reading required for double check valve only.
**** Indicates additional information not present on the standard TCEQ report