City of Georgetown - Backflow Prevention Assembly Test and Maintenance Report

The following form must be completed for each assembly tested for recordkeeping *purposes:

 City of Georgetown
 PWS ID:
 2460001

 PO Box 1430
 Contact Name:
 Water Regulatory

Georgetown, Texas 78626 Phone Number: 512-930-3640

BPAT Information

Company Name: Safewater Backflow and Irrigation Phone Number: 5126059790

 Tester Name:
 Brad Weyant
 Email Address:
 brad@safewateratx.com

 Address:
 609 E 50TH
 License Number:
 BP0016935

Location Information Contact Information

Property Type: Residential Company Name:

Business Name: Contact Name:

Business Name: Contact Name:
Property Address: 501 Blue Jasmine Trl Mailing Address:

Property Address:501 Blue Jasmine TrlMailing Address:501 Blue Jasmine TrlGeorgetown, TX 78628Georgetown, TX 78628

Phone Number: Email Address:

Backflow Information

The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters.

Backflow Method: Double Check Valve

Main Assembly Manufacturer: Apollo Model: DC4A Size: 1 Serial Number: 64101C

Location: Right front yard 5 feet from meter Hazard Type ****: Irrigation - Non Chemical

Backflow Test Information

Test Result: Passed
Reason for Test: New Installation

Is the assembly installed in accordance with manufacturers recommendations and/or local codes? Yes

Is the assembly installed on a non-potable water supply (auxiliary)? No

Differential pressure MidWest 845-5 (potable) Serial Number: 09231317 Date Tested for Accuracy: 3/14/2024

gauge used:

| | Double Check Valve | |
|-------------------------------|--------------------|------------------|
| | Check Valve #1 | Check Valve #2 |
| Initial Test | Held at 1.9 PSID | Held at 1.9 PSID |
| Date: 6/14/2024 | ✓ ClosedTight | ✓ ClosedTight |
| Time: 2:10 PM | Leaked | Leaked |
| Repairs and Materials Used | | |
| Repair Details | | |
| Test After Repairs | Held at 0 PSID | Held at 0 PSID |
| | Closed Tight | Closed Tight |
| | | |

Remarks

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS

^{*** 2}nd Check: Numeric reading required for double check valve only.

^{****} Indicates additional information not present on the standard TCEQ report