Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for record keeping *purposes:										
NAME OF PWS: Travis Cour			ity MU	y MUD 13						
PWS ID#:				Are Sta 1200 Aretin TV 70701						
	PWS MAILING ADDRESS: 100 Congress Ave PWS CONTACT PERSON: Backflow Reports					e Ste 1300 Austin, TX 78701				
ADDRESS OF SERVICE: 938 Bristol Creek Bend Lakeway, TX 78738										
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations										
and is certified to be operating within acceptable parameters.										
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):										
□ Reduced	d Pressure Principle (RPBA) 🔲 Reduced Pressure Principle-Detector (RPBA-D) Type II 🗌							D) Type II 🗆		
Double Check Valve (DCVA)				Double Check-Detector (DCVA-D) Type II						
Pressure Vacuum Breaker (PVB)Spill-Resistant Pressure Vacuum Breaker (SVB)								B)		
Manufacturer:Main: ApolloBypass:Size:Main: 1"Bypass:										
=			Bypass:		BPA Location: Right front yard 10 feet from meter					
Serial Number:	-			BPA Serves: Irrigation						
Reason for test: New Existing Replacement Old Model/Serial #										
Is the assembly installed in accordance with manufacturer recommendations and/or local codes? Xes No										
Is the assembly installed on a non-potable water supply (auxiliary)?										
TEST RESULT Type II										
		ure Principle	Assem	bly (RPBA)	Assembly		PVB & SVB			
PASS 🛛	ASS 🛛 DCVA				Developed Charals		A : T 1 4	Charle Value		
FAIL	1 st Check 2 nd Check***			Kener valve	Bypass Check		Air Inlet Check Valve			
Date: 8/2/2024 psid Time: 2:30PM Closed Tickt		Held at2 Closed Tight Leaked	-	psid Did not	Held at _ Closed T Leaked	ight 🗌	-			
Repairs and	Main:			<u> </u>		<u> </u>	<u> </u>	·		
Materials Used** Bypass:										
Tost After	• •	1 11 11	• 1	0 1 /	TT 11 4	. 1	0 1 /	· 1 II 11 /		
<u>Test After</u> <u>Repair</u> Date: Time:	Held at psi Closed Tight		-	*	Closed Tight		Opened at	_psid Held at psid		
*** 2 nd check: numeric reading required for DCVA only										
Differential pressure gauge used:							Non-Potable:			
Make/Model:	09231317 Date tested			ted for accura	cy: 3/14/2024					
Remarks:										
Company Name: Safewater Backflow				Licensed Tester Name Brad Weyant (Print/Type):						
Company Address: PO Box 44 78765				Licensed Tester Name (Signature):						
Company Phone #:512-605-9790BPAT License #BP0016935License Expiration Date:12/3/2024						/ -				
× •				- •						

ie at the time of testing.

The above is certified to be true at the time of testin * TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)] ** USE ONLY MANUFACTURER'S REPLACEMENT PARTS