City of Georgetown - Backflow Prevention Assembly Test and Maintenance Repor

| | City of Georgetown - Ba | ickflow Prevention Assembly 1 | est and maintenance report |
|--|---|---|--|
| The following form must | be completed for each assembly test | ed for recordkeeping *purposes: | |
| | City of Georgetown PO Box 1430 Georgetown, Texas 78626 | PWS ID: Contact Name: Phone Number: | 2460001 Water Regulatory 512-930-3640 |
| | | BPAT Information | |
| Company Name: Tester Name: Address: | L Sinclair Services, Inc. Lewis Sinclair 1307 Machado Road Cedar Park, Texas 78613 Location Information | Phone Number: Email Address: License Number: License Expiratio | |
| Property Type: Business Name: Property Address: | Residential 1005 Calendula Trl Georgetown, TX 78628 | Company Name: Contact Name: Mailing Address: Phone Number: Email Address: | |
| acceptable parameters. Backflow Method: Main Assembly Manuf Location: | Double Check Valve facturer: Apollo 4' W of Water Meter | Backflow Information ested and maintained as required by com Model: DC4A Size: 1 | mission regulations and is certified to be operating within Serial Number: 85665C |
| Hazard Type ****: | Irrigation - Non Chemical | Backflow Test Information | |
| Test Result: Reason for Test: Is the assembly instal | Passed New Installation led in accordance with manufacture | ers recommendations and/or local code | es? Yes |
| Is the assembly install Differential pressure gauge used: | led on a non-potable water supply (Mid-West 845-3 (potable) | Serial Number: 10200408 | Date Tested for Accuracy: 2/27/2024 |
| | Dou Check Valve #1 | uble Check Valve Check Valve #2 | |
| Initial Test Date: 12/18/2024 Time: 12:30 PM Repairs and | Held at 1.8 PSID ☑ ClosedTight ☐ Leaked | Held at 2 PSID ClosedTight Leaked | |
| Materials Use Repair Detail Test After Repa | s | Held at 0 PSID | |

Remarks

The above is certified to be true at the time of testing.

* TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC 290.46(B)]

** USE ONLY MANUFACTURER'S REPLACEMENT PARTS

*** 2nd Check: Numeric reading required for double check valve only.