City of Georgetown - Backflow Prevention Assembly Test and Maintenance Report The following form must be completed for each assembly tested for recordkeeping *purposes: City of Georgetown PWS ID: 2460001 Water Regulatory PO Box 1430 **Contact Name:** 512-930-3640 Georgetown, Texas 78626 Phone Number: **Phone Number:** 512-563-8762 L Sinclair Services, Inc. Company Name: **Email Address:** Iss@austin.rr.com Lewis Sinclair **Tester Name:** License Number: BP0002815 Address: 1307 Machado Road 2/12/2026 Cedar Park, Texas 78613 License Expiration: Residential Company Name: **Property Type:** Contact Name: **Business Name:** 1101 White Daisy Ln 1101 White Daisy Ln Mailing Address: **Property Address:** Georgetown, TX 78628 Georgetown, TX 78628 Phone Number: Email Address: Backflow Information The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters. **Backflow Method:** Double Check Valve Serial Number: 88615C Model: DC4A Size: 1 Main Assembly Manufacturer: Apollo Location: 5' WSW of Water Meter Hazard Type ****: Irrigation - Non Chemical Backflow Test Information **Test Result:** Passed Reason for Test: **New Installation** Is the assembly installed in accordance with manufacturers recommendations and/or local codes? Yes Is the assembly installed on a non-potable water supply (auxiliary)? No 2/27/2024 **Date Tested for Accuracy:** Mid-West 845-3 (potable) Serial Number: 10200408 Differential pressure

| | Double Check Valve | |
|-------------------------------|--------------------|----------------|
| | Check Valve #1 | Check Valve #2 |
| Initial Test | Held at 2.1 PSID | Held at 2 PSID |
| ate: 12/12/2024 | ✓ ClosedTight | ✓ ClosedTight |
| Fime: 1:40 PM | Leaked | Leaked |
| Repairs and Materials Used | | |
| Repair Details | | |
| Test After Repairs | Held at 0 PSID | Held at 0 PSID |
| | Closed Tight | Closed Tight |
| | | |

The above is certified to be true at the time of testing.

* TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC 290.46(B)]

** USE ONLY MANUFACTURER'S REPLACEMENT PARTS

*** 2nd Check: Numeric reading required for double check valve only.

**** Indicates additional information not present on the standard TCEQ report