## Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form mu		each assembly tested. A sign				for recordkeeping *purposes:	
NAME OF PWS:		Travis County MUD 2					
PWS ID#:		2270403					
PWS MAILING			502 San Juan Dr. Austin, TX 78733				
PWS CONTACT PERSON:		Backflow Reports					
ADDRESS OF S			17125 Sanglier Drive Austin, TX 78738				
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations							
and is certified to be operating within acceptable parameters. TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):							
Reduced Pressure Principle (RPBA)       Reduced Pressure Principle-Detector (RPBA-D)       Type II							
	Check Valve (D	• • • • –	Double Check-Detector (DCVA-D)     Type II				
		,	Spill-Resistant Pressure Vacuum Breaker (SVB)				
Pressure Vacuum Breaker (PVB)Spill-Resistant Pressure Vacuum Breaker (SVB)							
Manufacturer: Main: Apollo		Bypass:		Size:	Main: 1" Bypass:		
Model Number: Main: DC4A		Bypas	55:	BPA Location:		d 10 ft from meter	
Serial Number:	Main: 887310	C Bypass:	BPA Serves: Irrigation				
Reason for test:    New 🛛    Existing □    Replacement □    Old Model/Serial #							
Is the assembly installed in accordance with manufacturer recommendations and/or local codes? $\square$ No							
Is the assembly	installed on a ne	on-potable water sup	ply (auxiliary)?			□ Yes ⊠ No	
TEST RESULT				Type II			
TEST RESULT	Reduced Press	ure Principle Assem	blv (RPBA)	Assembly	ру	PVB & SVB	
		-					
PASS 🛛		DCVA	Relief Valve	Bypass Check	Air Inlet Check Valve		
FAIL	1 <sup>st</sup> Check	2 <sup>nd</sup> Check***		Dypuss cheek			
Initial Test	Held at 1.7	Held at 2.0 psi	d Opened at	Held at psid	Opened at	psid Held at	
Date:	psid Closed Tight		psid	Closed Tight	Did not open	psid	
12/13/2024 Closed Tight			Did not	Leaked	Did it fully open Leaked		
Time: 1:40PM	Leaked [		open		(Yes 🛛 /No 🗖	1)	
Repairs and   Main:     Materials							
							Used**
Test After	Held at p	sid Held at psid	Opened at	Held at psid	Opened at	psid Held at	
Repair	Closed Tight	1 · · · · · · · · · · · · · · · · · · ·		Closed	1	psid	
Date:			J	Tight 🛛			
Time:							
*** 2 <sup>nd</sup> check: numeric reading required for DCVA only							
Differential pressure gauge used:			Potable: 🛛 1		Non-Potable:		
Make/Model: MidWest 845 SN:			09231317 Date tested		ted for accurac	ed for accuracy: 3/14/2024	
Remarks:							
Company Name: Safewater Backflow Licensed Tester Name Brad Weyant						ant	
				(Print/Type):			
Company Addre		s: PO Box 4002 Austin, TX		Licensed Tester Name (Signature):			
78765							
Company Phone #: 512-605-9		9790	BPAT License # BP0016935				
License Expiration Date: 12/3/2027							
The above is certified to be true at the time of testing.							

\* TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)] \*\* USE ONLY MANUFACTURER'S REPLACEMENT PARTS