Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping *purposes:

NAME OF PWS:				Round Rock Water								
PWS ID#:				2460003								
PWS MAILING ADDRESS:				3400 Sunrise Rd Round Rock, TX 78665								
PWS CONTACT PERSON:				Inspections								
ADDRESS OF SERVICE: 1804 Homestead Farms Dr. Round Rock, TX 78681												
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters.												
and is	certified	to be					IONI A GO	TO ADT Y	7 (DD 4)		1	
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA): Reduced Pressure Principle (RPBA) Reduced Pressure Principle-Detector (RPBA-D) Type II												
			• • •			Reduced Pressure Principle-Detector (RPBA-D) Type II						
\boxtimes			x Valve (DC	*	bouote enect			x-Detector (DCVA-D) Type II □				
	Pressure	Vacuum Breaker (PVB)				Spill-Resistant Pressure Vacuum Breaker (SVB)						
									D			
Manufacturer:		Main: Apollo Main: DC4A		Bypa			Size:		Main: 1" Bypass: Left front yard 5 feet from meter			
Model Number Serial Number:		Main: DC4A Main 88796C		Bypass:			BPA Location: BPA Serves:		Irrigation			
Seriai	Number:	IVI	alli 88/90C		ypass:	BPA Serves: Imgauon						
Reason for test: New ☐ Existing ☐ Replacement ☐ Old Model/Serial #												
Is the assembly installed in accordance with manufacturer recommendations and/or local codes?										Yes \square No		
Is the	assembly	insta	lled on a no	n-potable v	vater si	upply (auxiliary)?					Yes 🛮 No	
									103 2 110			
TEST RESULT PASS		Reduced Pressure Principle Assen				-1-1 (DDD A)	Type II Assembly		PVB & SVB		CVD	
						IDIY (KPDA)					SVD	
		DCVA										
FAIL		1st Check 2nd Check**			-***	Relief Valve	Bypass Check				Check Valve	
FAIL 🗆		1 Cheek										
Initial Test Date: 7/16/2024 Time: 2:50PM		Held at 2.2 psid Held at _2.2			2 psid	_	Held at psid		Opened at psid			
		Close	ed Tight 🛮	Closed Tight 🛮 Leaked		psid Did not	Leaked \Box		Did not open		psid	
		Leak	ed \square						Did it fully open	· ·		
						open \square			(Yes □ /No □)			
Repairs and Materials Used**		Mair	ı.	1		·						
		AVAMAIA.										
		Bypass:										
Togt A	fton			TT -1.1 - 4		01-4	II-1-1 - 4	:1	01	: .1	TT-14 -4	
Test After Repair Date:		Held		Held at psid Closed Tight		_	Held at psid Closed Tight \square		Opened atpsid		Held at	
		Clos	ea right \square			psid					psid	
Time:							11giii 🗀					
		***	2nd check	numeric res	ding r	equired for DC	VA only	<u> </u>				
*** 2 nd check: numeric reading required for DCVA only Differential pressure gauge used: Potable: Non-Potable:												
					SN:	Potable: Dota to			ted for accuracy: 3/14/2024			
Make/Model: Mid West 845			1 West 845		SIV:	09231317 Date te		sted 101 accuracy. 3/14/2024				
Remarks: Permit#												
Comp	any Nam	e: Safewater Backflow				Licensed Tester Name Brad Weyant						
FJ 1.wiii						(Print/Type):						
Company Addre		ess: PO Box 40 78765		002 Austin, TX		Licensed Tester Name (Signature):						
												Comp
License Expiration Date: 12/3/2024												
			-			ind to be true o			•			

The above is certified to be true at the time of testing.

^{*} TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)]

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS