Texas Commission on Environmental Quality

BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

| The following form mu | | | | | ust be subm | itted to the p | oublic water supplier | for recordkeep | oing *purposes: | |
|---|--|-----------------------|--|-----------------------------------|-------------------------|----------------------|-----------------------|--------------------------------------|-----------------|--|
| NAME OF PWS: | | Round Rock Water | | | | | | | | |
| PWS ID#: | | 2460003 | | | | | | | | |
| PWS MAILING | 3400 Sunrise Rd Round Rock, TX 78665 | | | | | | | | | |
| PWS CONTAC | Inspections 1935 Homostood Forms Drive Round Book, TV 79691 | | | | | | | | | |
| ADDRESS OF S | 1835 Homestead Farms Drive Round Rock, TX 78681 | | | | | | | | | |
| The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters. | | | | | | | | | | |
| TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA): | | | | | | | | | | |
| Reduced Pressure Principle (RPBA) Reduced Pressure Principle-Detector (RPBA-D) Type II | | | | | | | л | | | |
| ☐ Reduced☐ Double C | , — | | | | | • • | | | | |
| | | | Double Check-Detector (DCVA-D) Spill-Resistant Pressure Vacuum Breaker (SVB) Type II □ | | | | | | | |
| Pressure Vacuum Breaker (PVB) Spill-Resistant Pressure Vacuum Breaker (SVB) | | | | | | | | | | |
| Manufacturer: | cturer: Main: Apollo | | | ss: | Size: | | Main: [1"] | Main: [1"] Bypass: | | |
| Model Number: | per: Main: DC4A | | Bypass: | | BPA Location: | | Right front ya | Right front yard 5 feet from meter | | |
| Serial Number: | r: Main 94111C Bypass | | | BPA Serves: Irriga | | | Irrigation | gation | | |
| | | | | | | | | | | |
| Reason for test: New ⊠ Existing □ Replacement □ Old Model/Serial # | | | | | | | | | | |
| Is the assembly installed in accordance with manufacturer recommendations and/or local codes? | | | | | | | | | | |
| Is the assembly i | | | | ar codes. | | | | | | |
| <u> </u> | instance on a no | i-potable wat | ci sup | pry (auxiliary): | | | | ☐ Yes | ⊠ No | |
| TEST RESULT | | | | | Type II | | | | | |
| | Reduced Pressu | re Principle A | oly (RPBA) | Assembly | | PVB & SVB | | 3 | | |
| PASS 🖾 | | CVA | | Bypass Check | | Air Inlet Check Valv | | | | |
| FAIL D | 1st Check | 2 nd Check | Relief Valve | | | | | heck Valve | | |
| Initial Test | Held at 1.9 psid | Held at 1. | 7 psid | Opened at | Held at | psid | Opened at | psid Held | l at | |
| Date: | Closed Tight Closed Tight | | | psid | | | Did not open psid | | | |
| 10/172024 | Leaked | Leaked | | Did not | Leaked | | Did it fully open | Leal | ced 🔲 | |
| Time: 9:30AM | | Deaked | [—] | open | Leaked | | (Yes □ /No □ | 1) | , , | |
| Danairs and | Main: | | | | | | | r | | |
| Repairs and Main: Main: Main: | | | | | | | | | | |
| Used** | | | | | | | | | | |
| | , , | 1 77 11 | 1 | | TT 11 . | 1 | 0 1 | | • . [| |
| Test After | | d Held at | _ psid | Opened at | | | Opened at | psid Held | psid | |
| <u>Repair</u> Date: | Closed Tight | | psid | Closed | | | psid | psid | | |
| Time: | | | | | Tight | 4 | | | | |
| | | | | | | | | | | |
| *** 2 nd check: numeric reading required for DCVA only Differential pressure gauge used: Potable: Non-Potable: | | | | | | | | | | |
| Make/Model: Mid West 845 SN: | | | CNI. | Potable: 2 09231317 | L L | Data tas | | Non-Potable: d for accuracy: 3/14/2 | | |
| Make/Model. | 09231317 Date tested 10 | | | ned for accurac | 101 accuracy. 3/14/2024 | | | | | |
| Remarks: Permit# | | | | | | | | | | |
| | | | | | | | | | | |
| Company Name: | Backflow | | Licensed Tester Name (Print/Type): Brad Weyant • | | | | | | | |
| Company Address: PO Box 40 78765 | | 002 Austin, TX | | Licensed Tester Name (Signature): | | | | | | |
| Company Phone | #: 512-605-9 | 790 | | BPAT License # BP0016935 | | | | | | |
| License Expiration Date: 12/3/2024 | | | | | | | | | | |
| The above is certified to be true at the time of testing | | | | | | | | | | |

^{*} TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)] ** USE ONLY MANUFACTURER'S REPLACEMENT PARTS