City of Georgetown - Backflow Prevention Assembly Test and Maintenance Report

The following form must be completed for each assembly tested for recordkeeping *purposes:

 City of Georgetown
 PWS ID:
 2460001

 PO Box 1430
 Contact Name:
 Water Regulatory

Georgetown, Texas 78626 Phone Number: 512-930-3640

BPAT Information

Company Name: Safewater Backflow and Irrigation Phone Number: 5126059790

 Tester Name:
 Brad Weyant
 Email Address:
 brad@safewateratx.com

 Address:
 609 E 50TH
 License Number:
 BP0016935

 609 E 50TH
 License Number:
 BP0016935

 AUSTIN, Texas 78751
 License Expiration:
 12/3/2024

Location Information Contact Information

Property Type: Residential Company Name:

Business Name: Contact Name:

Property Address: 2225 Western View Dr Mailing Address:

2225 Western View Dr Mailing Address: 2225 Wester
Georgetown, TX 78626 Georgetown, TX 78626

Phone Number:

Email Address:

Backflow Information

The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters.

Backflow Method: Double Check Valve

Main Assembly Manufacturer: Apollo Model: DC4A Size: 1 Serial Number: 94150C

Location: Right front yard 5 feet from meter
Hazard Type ****: Irrigation - Non Chemical

Backflow Test Information

Test Result: Passed
Reason for Test: New Installation

Is the assembly installed in accordance with manufacturers recommendations and/or local codes? Yes

Is the assembly installed on a non-potable water supply (auxiliary)? No

Differential pressure MidWest 845-5 (potable) Serial Number: 09231317 Date Tested for Accuracy: 3/14/2024

gauge used:

	Double Check Valve	
	Check Valve #1	Check Valve #2
Initial Test	Held at 1.8 PSID	Held at 2 PSID
Date: 10/9/2024	✓ ClosedTight	✓ ClosedTight
Time: 9:30 AM	Leaked	Leaked
Repairs and Materials Used		
Repair Details		
Test After Repairs	Held at 0 PSID	Held at 0 PSID
	Closed Tight	Closed Tight

Remarks

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS

^{*** 2}nd Check: Numeric reading required for double check valve only.