City of Georgetown - Backflow Prevention Assembly Test and Maintenance Report

The following form must be completed for each assembly tested for recordkeeping *purposes:

City of Georgetown **PWS ID**: 2460001

PO Box 1430 Contact Name: Water Regulatory Georgetown, Texas 78626 Phone Number: 512-930-3640

BPAT Information

Company Name: Safety Plus Services, LLC. Phone Number: 512-300-9659

Tester Name: Scott Stevenson Email Address: scott@safetyplusservices.com

Address: 102 Wonder World Drive, Suite #304-522 License Number: BP0017507
San Marcos, Texas 78666 License Expiration: 12/19/2025

Location Information Contact Information

Property Type: Residential Company Name: Tri Point Homes

Business Name: Contact Name:

Property Address: 236 Cactus Tower Path Mailing Address: 236 Cactus Tower Path

Georgetown, TX 78628 Georgetown, TX 78628 Phone Number:

Email Address:

Backflow Information

The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters.

Backflow Method: Double Check Valve

Main Assembly Manufacturer: Apollo Model: DC4A Size: 1 Serial Number: 88588C

Location: Front left 5' from meter **Hazard Type** *****: Irrigation - Non Chemical

Backflow Test Information

Test Result: Passed
Reason for Test: New Installation

Is the assembly installed in accordance with manufacturers recommendations and/or local codes? Yes

Is the assembly installed on a non-potable water supply (auxiliary)? No

Differential pressure BacFlo Unlimited Bac Flo 5 (potable) Serial Number: 06163433 Date Tested for Accuracy: 10/11/2023

gauge used:

	Double Check Valve	
	Check Valve #1	Check Valve #2
Initial Test	Held at 1.8 PSID	Held at 2 PSID
Date: 8/26/2024	✓ ClosedTight	✓ ClosedTight
Time: 1:52 PM	Leaked	Leaked
Repairs and Materials Used		
Repair Details		
Test After Repairs	Held at 0 PSID	Held at 0 PSID
	Closed Tight	Closed Tight

Remarks

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS

^{*** 2}nd Check: Numeric reading required for double check valve only.