City of Kyle - Backflow Prevention Assembly Test and Maintenance Report

The following form must be completed for each assembly tested for recordkeeping *purposes:

City of Kyle	**PWS ID:**	1050002
520 E RR 150	**Contact Name:**	Mickal Morrison
Kyle, Texas 78640	**Phone Number:**	737-877-2927

BPAT Information

Company Name:	Safewater Backflow and Irrigation	**Phone Number:**	5126059790
Tester Name:	Brad Weyant	**Email Address:**	brad@safewateratx.com
Address:	609 E 50TH	**License Number:**	BP0016935
	AUSTIN, Texas 78751	**License Expiration:**	12/3/2024

Location Information / Contact Information

Property Type:	Residential	**Company Name:**	
Business Name:		**Contact Name:**	
Property Address:	315 Jackson River Loop	**Mailing Address:**	315 Jackson River Loop
	Kyle, TX 78640		Kyle, TX 78640
		Phone Number:	
		Email Address:	

Backflow Information

The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters.

Backflow Method: Double Check Valve

Main Assembly Manufacturer: Apollo **Model:** DC4A **Size:** 1 **Serial Number:** 01550D

Location: Right front yard 10 feet from meter

Hazard Type **:** Irrigation - Non Chemical

Backflow Test Information

Test Result: Passed

Reason for Test: New Installation

Is the assembly installed in accordance with manufacturers recommendations and/or local codes? Yes

Is the assembly installed on a non-potable water supply (auxiliary)? No

Differential pressure gauge used: MidWest 845-5 (potable) **Serial Number:** 09231317 **Date Tested for Accuracy:** 3/14/2024

	Double Check Valve	
	Check Valve #1	**Check Valve #2**
Initial Test **Date: 10/8/2024** **Time: 11:00 AM**	Held at 2.2 PSID ☑ ClosedTight ☐ Leaked	Held at 2.1 PSID ☑ ClosedTight ☐ Leaked
Repairs and Materials Used		
Repair Details		
Test After Repairs	Held at 0 PSID ☐ Closed Tight	Held at 0 PSID ☐ Closed Tight

Remarks

The above is certified to be true at the time of testing.
* TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC 290.46(B)]
** USE ONLY MANUFACTURER'S REPLACEMENT PARTS
*** 2nd Check: Numeric reading required for double check valve only.
**** Indicates additional information not present on the standard TCEQ report