Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping *purposes:

NAME OF PW	S:	WICPUA					
PWS ID#:		2270235					
PWS MAILING ADDRESS:		13215 Bee Cave Pkwy Building B Suite 110 Bee Caves, TX 7738					
PWS CONTACT PERSON:		WTCPUA Backflows					
ADDRESS OF SERVICE:		386 Old Stone Rd. Austin, TX 78738					
The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations							
and is certified to be operating within acceptable parameters.							
TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA):							
☐ Reduced Pressure Principle (RPBA) ☐			Reduced Pressure Principle-Detector (RPBA-D) Type II				
☐ Double Check Valve (DCVA)		′ –	Double Check-Detector (DCVA-D) Type II □				
☐ Pressure Vacuum Breaker (PVB) ☐ Spill-Resistant Pressure Vacuum Breaker (SVB)							
_		Вура					
Model Number: Main:DC4A		Bypass	:	BPA Location	: Left front yar	rd 5 feet from meter	
Serial Number: Main 88868C		Bypass:		BPA Serves:	es: Irrigation		
Reason for test: New ⋈ Existing □ Replacement □ Old Model/Serial #							
Is the assembly installed in accordance with manufacturer recommendations and/or local codes?							
Is the assembly installed on a non-potable water supply (auxiliary)? ☐ Yes ☐ No							
TEST RESULT				Type II			
		ure Principle Asser	mbly (RPBA)	Assembly	PVB & SVB		
		<u> </u>		,			
PASS ⊠ FAIL □	DCVA 1st Check 2nd Check***		Relief Valve	Bypass Check	Air Inlet	Check Valve	
<u>Initial Test</u>	Held at _2.0psid	_	Opened at	Held at psid	Opened at	_psid Held at	
Date: 7/3/2024	Closed Tight 🛛	Closed Tight	psid Did not	Closed Tight	Did not open	psid	
Time: 5:30PM	Leaked [Leaked \Box	_	Leaked \Box	Did it fully oper	Leaked \square	
			open \square		(Yes □ /No □])	
Repairs and	Repairs and Main:						
Materials							
Used** Bypass:							
Test After		d Held at psic	Opened at	Held at nsid	Opened at	psid Held at	
Repair		Closed Tight	1 -	Closed	Sp	psid psid	
Date:	Closed Fight L		1	Tight □			
Time:				118111			
*** 2 nd check: numeric reading required for DCVA only							
Differential pressure gauge used:			Potable: Non-Potable				
Make/Model: MidWest 845 SN:			09231317 Date tested for accu		sted for accura	cy: 3/14/2024	
Remarks:							
Company Name	e: Safewater	Backflow	Licensed Tester Name Brad Weyant				
			(Print/Type):				
Company Addr				Licensed Tester Name (Signature):			
	78765		17/1				
Company Phone #: 512-605-9790 BPAT License # BP0016935							
License Expiration Date: 12/3/2024 The above is certified to be true at the time of testing							
	r	l'ha ahava ic carti	had ta ha trua c	at the time of test	tina		

^{*} TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290.46(B)]

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS