City of Georgetown - Backflow Prevention Assembly Test and Maintenance Report

The following form must be completed for each assembly tested for recordkeeping *purposes:

City of Georgetown 2460001

PO Box 1430 **Contact Name:** Water Regulatory Georgetown, Texas 78626 Phone Number: 512-930-3640

BPAT Information

Company Name: Safewater Backflow and Irrigation

Brad Weyant Tester Name:

609 E 50TH AUSTIN, Texas 78751

Phone Number: 5126059790

Email Address: brad@safewateratx.com License Number: BP0016935

License Expiration: 12/3/2024

Contact Information

Property Type: Residential **Company Name: Business Name:** Contact Name:

Property Address: 513 Ahern Ct **Mailing Address:**

Liberty HIII, TX 78642

Phone Number: **Email Address:**

Georgetown, TX 78642

Date Tested for Accuracy:

3/14/2024

513 Ahern Ct

The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters.

Backflow Method: Double Check Valve

Main Assembly Manufacturer: Apollo Model: DC4A Size: 1 Serial Number: 88548C

Location: Right front yard 5 feet from meter Hazard Type ****: Irrigation - Non Chemical

Test Result: Passed **New Installation** Reason for Test:

Is the assembly installed in accordance with manufacturers recommendations and/or local codes? Yes

Is the assembly installed on a non-potable water supply (auxiliary)? No

Differential pressure gauge used:

Address:

MidWest 845-5 (potable) Serial Number: 09231317

	Double Check Valve	
	Check Valve #1	Check Valve #2
Initial Test	Held at 1.7 PSID	Held at 2.2 PSID
Date: 10/18/2024	✓ ClosedTight	✔ ClosedTight
Time: 1:25 PM	Leaked	Leaked
Repairs and Materials Used		
Repair Details		
Test After Repairs	Held at 0 PSID	Held at 0 PSID
	Closed Tight	Closed Tight

Remarks

The above is certified to be true at the time of testing.

* TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC 290.46(B)]

** USE ONLY MANUFACTURER'S REPLACEMENT PARTS

*** 2nd Check: Numeric reading required for double check valve only.