City of Kyle - Backflow Prevention Assembly Test and Maintenance Report

The following form must be completed for each assembly tested for recordkeeping *purposes:

 City of Kyle
 PWS ID:
 1050002

 520 E RR 150
 Contact Name:
 Mickal Morrison

 Kyle, Texas 78640
 Phone Number:
 737-877-2927

BPAT Information

Company Name: Safety Plus Services, LLC.

Tester Name: Scott Stevenson

Address: 102 Wonder World Drive, Suite #304-522

San Marcos, Texas 78666

Phone Number: 512-300-9659

Email Address: scott@safetyplusservices.com

License Number: BP0017507 License Expiration: 12/19/2025

ocation Information Contact Information

Property Type: Residential Company Name:

Business Name: Contact Name: Property Address: 578 Jackson River Loop Mailing Address

578 Jackson River Loop
Kyle, TX 78640

Mailing Address: 578 Jackson River Loop
Kyle, TX 78640

Kyle, TX 78640

Phone Number:

Email Address:

Backflow Information

The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters.

Backflow Method: Double Check Valve

Main Assembly Manufacturer: Apollo Model: DC4A Size: 1 Serial Number: 642660

Location: At meter

Hazard Type ****: Irrigation - Non Chemical

Backflow Test Information

Test Result: Passed
Reason for Test: New Installation

Is the assembly installed in accordance with manufacturers recommendations and/or local codes? Yes

Is the assembly installed on a non-potable water supply (auxiliary)? No

Differential pressure BacFlo Unlimited Bac Flo 5 (potable) Serial Number: 06163433 Date Tested for Accuracy: 10/11/2023

gauge used:

	Double Check Valve	
	Check Valve #1	Check Valve #2
Initial Test	Held at 1.8 PSID	Held at 2.2 PSID
Date: 6/30/2024	✓ ClosedTight	✓ ClosedTight
Time: 4:41 PM	Leaked	Leaked
Repairs and Materials Used		
Repair Details		
Test After Repairs	Held at 0 PSID	Held at 0 PSID
	Closed Tight	Closed Tight

Remarks

^{**} USE ONLY MANUFACTURER'S REPLACEMENT PARTS

^{*** 2}nd Check: Numeric reading required for double check valve only.